PRODUCT BULLETIN

Southern
TEXTILE CORPORATION

P.O. Box 32427
Charlotte, N. Carolina 28232

PLAINTIFF'S EXHIBIT
SB-21

ASBESTOS TAPES

GENERAL SPECIFICATIONS:

DESCRIPTION: Asbestos Tapes are composed of two main types -- Plain and Metallic. Some of the recommended uses for Plain Tapes are: wrapping armatures, electrical wire and cables, switchboard leads, bus bars, underground cables, as insulation for pipe hangars, as safety protection for covering hot piping, as stress relieving pads in welding operations, and as a component in packings and gaskets. Some of the recommended uses for Metallic Tapes are: brake linings and clutch facings, and as oil burner wicking.

COMPOSITION: Plain Tapes are composed of Asbestos fibers and synthetic.

Metallic Tapes are composed of Asbestos fiber, synthetic fiber, and special alloy wires. Both Plain and Metallic Tapes come in four (4) grades - Commercial, Underwriters, AA, and AAA.

PHYSICAL PROPERTIES: Service temperature up to 750°F. (Depending on grade).
CLEANGARD Processed to help meet requirements of OSHA.
Shrink-Pac to assure a clean appearance regardless of shelf life.
Available in colors on request.
Both Plain and Metallic Tapes can be made to meet the requirements of Mil Specs HHT-1782 and MIL-I-15399B.

DURABILITY: Asbestos Tapes are soft and pliable and easy to fabricate. They can be treated with numerous compounds to give additional heat resistance and abrasion resistance. Such treatments are available on request.

ADDITIONAL TYPES OF TAPES: The following types of Tapes are non-standard items but are available on request. Web Center Tape (Drop Warp), Tadpole Tape (Woven) and Oil Burner Wicking (Metallic).

WIDTHS: Asbestos Tapes are available in widths ranging from 1/2" to 12".

THICKNESSES: Non-Metallic Asbestos Tape is available in thicknesses from 1/32" to 1/4". Metallic Tape is available in thicknesses 1/16" to 1/4" thick. Greater thicknesses are available for industrial and special applications.

ROLL LENGTHS: 25 - 100 feet (depending on Tape thickness).