

NEG. NO. U-3A

TRADEMARK FILE INFORMATION

Trademark:	Fibrex
Trademark Owner:	The Flintkote Company
Last Assignee:	None
Date of First Use in Commerce:	June, 1940
Registration No.:	401,412
Date Trademark Registered:	May 18, 1943
Size of Label in Trademark File:	14.9375 x 8 inches



Receipt of Pictured Label by Patent Office:

CAUTION
COMBUSTIBLE MIXTURE
NYED C&A #1616

**FIBREX
CEMENT**
FOR COLD APPLICATION

DANGER
COMBUSTIBLE MIXTURE
CONTAINS PETROLEUM DISTILLATE
HARMFUL OR FATAL IF SWALLOWED
Avoid prolonged breathing of vapor or contact with skin.
Use only in well ventilated area.
If swallowed, do not induce vomiting.
Call a physician immediately.
Keep away from fire or open flame.
Keep can closed when not in use.
KEEP OUT OF REACH OF CHILDREN

USES
Fibrex Cement is an asphalt cement with quick setting, high strength characteristics, especially formulated for cementing between plies of coated roofing felt. It is also an excellent adhesive for the application of base sheets to roof surfaces. It replaces the conventional hot-poured cements used in industrial or commercial built-up roof construction. Refer to printed specifications for Flintkote Cold Process Systems.

DIRECTIONS
All surfaces to be coated must be dry, swept clean and free from oil, grease and debris. Stir in container and apply with three-knot roofing brush or spray at the rate of 1 1/2 gal. per 100 sq. ft. Apply at uniform film thickness and only a sufficient amount to completely cover sheets without any residue squeezing out at laps.

DANGER
CONTAINS PETROLEUM DISTILLATE
Read Carefully Other Cautions on Side Panel

FLINTKOTE
A GENSTAR COMPANY
NET: 5 Gallons (18.9 Liters)

ATTENTION!
THIS CONTAINER HAZARDOUS WHEN EMPTIED
Since Empty Containers Retain Product Residues (Vapor, Liquid or Solid), All Labeled Hazard Precautions **Must Be Observed**.
Do not expose to open flame.

Small text block containing legal disclaimer and safety information.

Distributed by
FLINTKOTE BUILDING PRODUCTS COMPANY
Marketing Division
580 Decker Drive - Irving, Texas 75062