

ONE

GALLON

Raise

by  O'BRIEN

"TOP QUALITY SINCE 1875"

EGGSHELL
HOUSE PAINT
TINTING WHITE

MADE BY THE O'BRIEN CORPORATION

SOUTH BEND, IND. • BALTIMORE, MD. • OKLAHOMA CITY, OKLA. • SAN FRANCISCO, CAL. • LOS ANGELES, CAL.

POISE EGGSHELL HOUSE PAINT

Poise Eggshell House Paint is a high quality, economy-priced outside paint with a pleasing low lustre. It is an all-purpose type finish for most surfaces—wood siding, wood and unglazed asbestos shingles, stucco, concrete, masonry (see *CAUTION), metal and trim. Available in White or Tinting White. Tinting White is a non-chalking finish for body or trim that may be tinted with Tone-All, with Oil Colors, or applied straight.

DIRECTIONS

Preparation—Surface must be clean and dry. Remove chalk and loose paint. Where moisture is present, ventilate behind siding. Repair flashings and structural defects.

Previously Painted Wood Shingles

Apply one coat of Poise Eggshell House Paint, thinned with one pint of linseed oil per gallon.

New Wood — Clapboard, Plywood, Masonite, Trim

Apply one coat of White Crest House Paint Primer White, thinned with two or three pints of linseed oil per gallon. Tint toward finish color. Finish with Poise Eggshell House Paint applied at package consistency.

Previously Painted Surfaces — Wood, Metal, Concrete, Masonry, Asbestos-Cement

Apply one coat of Poise Eggshell House Paint at package consistency. (Over badly weathered surfaces, prime first with White Crest House Paint Primer White at package consistency. Tint toward finish color.)

New Concrete, Masonry and Asbestos-Cement*

Apply one coat O'Brien A-R Primer. Tint toward finish color with Tone-All. Finish with Poise Eggshell House Paint applied at package consistency.

MADE IN U.S.A.

REC'D. NO. 25786

DATE 4-9-63

New Metal

Apply one coat of Tame Rust Metal Primer. Etch galvanized metal, such as gutters and downspouts, before priming. Finish with Poise Eggshell House Paint applied at package consistency.

Application—Apply Poise Eggshell House Paint by brush or spray at temperature not less than 60° F. Allow 48 hours good drying weather between coats. When necessary, thin sparingly with mineral spirits. Stir well before and during use.

Tinting—Do not use more than 4 ounces of Tone-All Colorant per gallon.

***CAUTION:** New masonry should be thoroughly dry before painting. Do not paint glazed type asbestos shingles! Do not paint chronically damp masonry.

DO NOT TAKE INTERNALLY
CAUTION! COMBUSTIBLE!
CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

POISE EGGSHELL HOUSE PAINT
Tinting White
100% Linseed Oil 14.00%
100% Linseed Oil 14.00%
100% Linseed Oil 14.00%
100% Linseed Oil 14.00%
100% Linseed Oil 14.00%
100% Linseed Oil 14.00%
100% Linseed Oil 14.00%

ONE

GALLON

For Better Decoration

Rise

by  **O'BRIEN**

"TOP QUALITY SINCE 1875"

WASHABLE FLAT WALL FINISH

LATEX

WHITE

MADE BY THE O'BRIEN CORPORATION

SOUTH BEND, IND. • BALTIMORE, MD. • OKLAHOMA CITY, OKLA. • SAN FRANCISCO, CAL. • LOS ANGELES, CAL.

POISE

Latex Flat Wall Paint

New POISE is an entirely new interior finish developed by O'Brien research—a perfected flat wall latex formulation for new high fashion beauty plus the advantages of... extra hiding... easier brush and roller application... fast 30 minute drying... true washability.

High quality POISE—in beautiful *fashion tint* colors is the best of all paint values.

DIRECTIONS FOR USE

Preparation—Surface should be washed perfectly free of kalsomine, dirt, grease, glue size or soluble casein paints. Cracks and nailholes should be filled with a patching plaster, and when dry, sanded smooth.

CAUTION—Glossy surfaces must be dulled by scrubbing with a scouring powder, steel wooling, sanding or by wiping with O'Brien's Tack-it.

New Unpainted Surfaces—1st coat, use new POISE. (Over unpainted wood or metal always use an O'Brien oil base primer before applying first coat of Poise). 2nd coat, use new Poise latex.

Previously Painted Surfaces—One coat of new POISE flat latex will do an excellent job. If the paint film is in bad condition or a radical change in color is made, apply two coats of new POISE.

REGISTERED

REC'D. No. 2513

DATE Y-1-63

Application — Apply generously and evenly with brush, roller or spray. If thinning is necessary, use only a small amount of clean water and stir thoroughly. Wipe splatters immediately with a damp cloth. Wash brush or roller cover in luke warm soapy water immediately after use.

On most surfaces new POISE latex may be washed off with a damp cloth. ~~After two coats, wash with a damp cloth.~~

Intermixing — New POISE latex colors may be intermixed. Do not tint with conventional paint or oil colors. Many beautiful Fashion Tints are available using O'Brien Tone-All Colors in White, Off White, Ivory and Medium Tone Tint Base. Do not use Tone-All Colorants in other standard colors.

NOTE—Allow 30 day curing before washing POISE.

DO NOT TAKE INTERNALLY
CAUTION!
Do not take internally. Close container after each use. KEEP OUT OF THE REACH OF CHILDREN.

POISE WHITE
Primary Colors
Yellow
Orange
Red
Violet
Blue
Green
Black
White
Tint Base
Medium Tone
Ivory
Off White
White

OTHER O'BRIEN PAINTS FAMOUS FOR SUPERIOR FINISHING

FLEXICO	PEN-CHROME	75 HOUSE PAINT
Super All-Purpose Enamel	Accent Stains for Natural Wood	Gloss or Eggshell

STIR PAINT WELL BEFORE USE. DO NOT THIN WITH PAINT SOLVENTS. KEEP FROM FREEZING.