(File 54251AA) Nov 20, 1964

MATERIAL 54251AA Abru AC

COMPOUND, INSULATING, THERMAL AND SOUND DEADENING

CAUTION: THIS IS GROUP 2A FLAMMABLE LIQUID. KEEP SPARKS AND FLAMES AWAY. DO NOT BREATHE VAPOR OR SPRAY MISTS. AVOID PROLONGED OR REPEATED CONTACT WITH THE SKIN. SEE SPDS C-18.

FURNISHED BY -

~~(A)Jamestown Finishes, Inc, 52 Angove, Jamestown, NY~~

(B)M B Suydam Div, Pgh Plate Glass Co, Preble Ave, Pittsburgh, Pa

ORDER FROM SUPPLIER AS -

~~(A)Sound Deadener MS 1-3780 R-2~~ 30 gal. drums

(B)Insulating Compound ~~10305-B~~ S-16337 ~~(2 lbs/gal)~~ (2.60/gal)

CHARACTERISTICS - ~~(54251AA)(Previous 4057-1)Canceled, obsolete.~~

~~(54251AB)(Previous 4057-2)Canceled, superseded by 46110BJ.~~

(54251AC)(Previous 4057-3)(User:PH)Heavy, brown insulating compound composed of inert fillers, asbestos fibers, and synthetic resin vehicle. Applied by spraying. It is nonflammable and has good heat resistance, sound deadening and insulating characteristics. INSULATION OF TURBINE ENCLOSURE

APPLICATION - ~~Turbine lagging insulation~~

SPECIFY AS - COMPOUND 54251AC

Issued by Corporate Standards, R&D Center, Pgh 35, Pa

Printed in U.S.A.

DOCUMENTS PRODUCED BY
DALLAS COUNTY CASES

PLAINTIFF'S EXHIBIT WH 84