

ONE

GALLON

 O'BRIEN'S

75⁰⁰

EXTERIOR EGGSHELL
PAINT

FOR WOOD AND ASBESTOS SHINGLES • MASONRY • SIDING

FLAME

MADE IN U.S.A. BY THE O'BRIEN CORPORATION • SOUTH BEND, INDIANA • BALTIMORE, MARYLAND

**For Wood & Asbestos Shingles—Stucco—
Concrete—Wood Siding and Trim**

A new, all-purpose outside eggshell paint for use on wood and asbestos shingles, stucco, concrete, masonry, metal, wood siding and trim. It provides a rich, durable finish is preferred to the conventional high luster. This material works easy under the brush; has excellent coverage and unsurpassed hiding. Made with Pre-Shrunk Oils, it beautifies, protects and waterproofs. A "breather type" paint — it reduces paint blistering and peeling.

O'Brien's "75" Exterior Eggshell Paint Sealer is a special clear sealer for mixing with the paint, making an excellent primer for use over stucco, concrete, shingles and other porous surfaces where a two coat job is necessary. It helps to prevent paint troubles due to varying porosity or the presence of free alkali in stucco and masonry surfaces.

THINNING NOTE — to retard drying and setup of paint during hot weather, one pint of "75" Ex. Egg. Pt. Thinner should be added to each gal. of paint.

CAUTION! COMBUSTIBLE
Keep Away from

Keep Away from

**Heat and Open Flame
CONTAINS LEAD OR OTHER
COMPOUNDS HARMFUL IF EATEN**
Do not apply on toys, furniture or
interior surfaces which might be
chewed by children. Use with ade-
quate ventilation. Avoid breathing
vapor or spray mist. Avoid pro-
longed contact with skin. Wash
thoroughly after handling. Do
not eat or smoke. Keep
container closed when not in use.

[illegible]

Asbestos Shingles (unpainted*) — two coats are necessary. Under pastel colors of "75." Exterior Eggshell, use a prime coat of O'Brien's A.R. Primer (may be tinted with Tone-All Colors, not more than two tubes per gal.) Under dark colors of Exterior Eggshell, use a prime coat consisting of equal part mixture of "75." Exterior Eggshell Paint Sealer and Exterior Eggshell Paint. Finish with one coat of "75." Exterior Eggshell Paint.

***IMPORTANT**—this material is not recommended for use over unpainted asbestos shingles unless the shingles have weathered at least five years. Do not use over glazed type shingles.

Asbestos Shingles (old, previously painted) surfaces in good condition normally require only one coat of "75" Exterior Eggshell. Over badly weathered surfaces, follow specifications under "Wood Shingles, Siding, Trim (New Unpainted)."

Wood Shingles, Siding, Trim (new, unpainted) — one coat "75" House Paint
Primer followed with one coat "75" Exterior Eggshell

Wood Shingles, Siding, Trim (previously painted) — same specifications as listed under "Asbestos Shingles (Old, Previously Painted)."

Stucco, Concrete, Masonry — follow same specifications as listed above under "Asbestos Shingles, Unpainted." NOTE—allow new masonry to age six months, if possible, before painting. Do not paint wet or chronically damp masonry with an oil base paint.

Special Note — before painting over stained shingles or shakes, paint a small test area and allow to dry several days to determine whether stain will "bleed" through. If no discoloration occurs, proceed with painting.

THE O'BRIEN CORPORATION
SOUTH BEND, IND. OKLAHOMA CITY, OKLA.
BALTIMORE, MD. SAN FRANCISCO, CAL.
LOS ANGELES, CALIF.

49 TOC 001141