

FROM PITTSBURGH PURCHASING  
INDUSTRIAL - 19

TO MEMORANDUM

October 4, 1972

RE: NATIONAL PURCHASE AGREEMENT P-615951  
JOHNS-MANVILLE SUPEREX INSULATION BLOCK

---

Johns-Manville has completed their development of an asbestos-free high temperature insulation block. This is welcomed news in light of our concern on OSHA standards involving the handling of asbestos type materials.

Beginning with October shipments, Johns-Manville will be filling all orders for Superex with either the present Superex material containing approximately 8% asbestos or the Asbestos-Free Superex. Until Johns-Manville's entire production capacity has been converted to the asbestos-free material, many orders may be mixed with both types of insulation block. During this conversion period, the Asbestos-Free Superex cartons will be stenciled with the suffix AF (Superex 2000 AF). When the transition is complete, the AF suffix will be dropped and all Johns-Manville Superex will be asbestos-free. Total conversion is expected on or before March 1, 1973.

The new Asbestos-Free Superex has a maximum use temperature of 2000°F and is superior to the present Superex with respect to both compressive strength and thermal conductivity. The transverse strength (modulus of rupture) of the new board is slightly less than that of the asbestos board, but this difference should have little effect on our applications. A copy of the properties of the new board is attached.

For the balance of our agreement period for Superex, the price of the new board will be the same as that for the present formulation of Superex. However, because of the higher cost ingredients in the new board, a price increase for Superex may be imminent when the present agreement expires on December 31, 1972.

For all future releases of Superex, do not specify "asbestos-free". The new material will be fed into your orders on the basis of the supply on hand at the time of your release.



ARD 007024

Memorandum  
October 4, 1972  
Page 2

We would appreciate your forwarding this information to your operating groups and, in particular, those concerned in policing OSHA standards.

M. J. CAPRIO

MJC/lmp

*mpc*

Attachment

Distribution:

R. D. Griswold - Alcoa, Tennessee  
H. A. Barton - Badin  
J. K. Chambers - Bauxite  
W. E. King - Cleveland  
A. E. Gantt - Cressona  
H. P. Brueschke - Davenport  
R. C. Miessler - Lafayette  
F. W. Hecker - Lancaster  
H. L. Gallop - Lebanon  
G. H. Duckworth - Massena  
J. V. Driscoll - Mobile  
R. N. Anderson - New Kensington (CMD)  
J. R. Zokaite - Point Comfort  
W. R. Eidson - Richmond  
G. R. Farneth - Rockdale  
D. J. Fisher - Vancouver  
C. A. Halliday - Vernon  
J. D. Eagan - Warrick  
C. J. Shank - Wenatchee  
O. E. Proctor - Alcoa Technical Center  
T. B. Weber - Corona  
H. T. Culver - ACPC - Marshall  
G. F. Leymeister - Pittsburgh, 19  
T. B. Bonney - Pittsburgh, 7

ARD 007025

J-M SUPEREX - ASBESTOS FREE  
(Preliminary Properties 9/11/72)

|                                                                         | <u>Suprex 2000 AF</u> |
|-------------------------------------------------------------------------|-----------------------|
| Density, lbs. per cubic foot                                            | 24                    |
| Modulus of rupture, psi                                                 | 65                    |
| Compressive strength, psi<br>at 5% deformation (2" thick)               | 150                   |
| Linear Shrinkage, % @ 2000°F                                            | 2.8                   |
| Maximum Service Temperature, °F<br>(in oxidizing atmosphere)            | 2000                  |
| Thermal Conductivity, BTU/In./Sq. Ft./°F/Hr.<br>at mean temperature, °F |                       |
| 400                                                                     | 0.59                  |
| 600                                                                     | 0.65                  |
| 800                                                                     | 0.70                  |
| 1000                                                                    | 0.77                  |