


HUBBELL CORPORATION

HAWLEY ROAD • MUNDELEIN, ILLINOIS

Telephone MUNdelein 6-7330 • Chicago, ROgers Park 1-1224

C & S Equipment Co., Inc.
Los Angeles, Calif.Shinwa Trading Co.
Tokyo, JapanJenkinson & Co., Ltd.
Toronto, CanadaH. W. Baker Co.
San Francisco, Calif.Groeneveld Van Der Poll & Co.
Amsterdam, HollandJaleel Bros.
Pakistan

SEVEN NEW SECTIONS

Solenoid Valves for Refrigeration
Solenoid Valves for Air, Water, Brine
Back Pressure Regulating Valves
Compensating Back Pressure Regulating Valves
Miscellaneous Accessories
Repair Parts and Kits
Engineering Data

TWENTY-FIFTH ANNIVERSARY—Catalog now available.

The new No. 57 Hubbell Catalog has seven complete and distinct sections. Each section describes in detail the construction of the controls—complete and detailed description together with application data. The engineering section contains completely new and original data and tables useful every day in the design and application of refrigeration systems.

The Hubbell line of controls consists of solenoid valves ranging from $\frac{1}{8}$ in. in size to 8 in. Solenoids are suitable for water, air, gas, oil, chemicals, and all types of refrigerants.

The Hubbell line of regulators is available in sizes $\frac{1}{2}$ in. to 8 in. inclusive. They are suitable for all types of refrigerants and are manufactured in many different types. Straight back pressure regulators, combination regulators and stop valves, reverse acting regulators, bottom seating regulators, dual pressure regulators, compensating regulators air operated, electrically operated and thermal operated, hot gas defrosting systems, constant liquid pressure controls, vacuum type regulators and many other special types and applications. Write for your copy of Catalog No. 57.

[HUBBELL-ize your plant with "Service Free" controls.]


Illinois Testing Laboratories, Inc.

Room 516, 420 N. La Salle St., Chicago 10, Ill.

Alnor

Precision Instruments for Every Industry



The direct-reading ALNOR VELOMETER



TYPE 4-F Standard minimum set for heating and air conditioning air velocity measurements.

The Alnor Velometer is an instantaneous, direct-reading air velocity meter designed for convenient, rapid determination of air velocities in air conditioning, heating and ventilating, and exhaust systems. It gives instantaneous direct readings in feet per minute, without timing, calculations, or reference to tables or charts. Accurate information on performance of equipment, duct systems, etc., can be obtained with a few moments inspection with the VELOMETER. It can be effectively used to locate drafts and leaks around windows and doors, or in duct systems.

The Alnor Velometer is built in several standard ranges from 20 fpm to 6000 fpm, and up to 3 in. static or total pressure. Special ranges available as low as 10 fpm and up to 25,000 fpm velocity and 20 in. pressure.



Alnor Velometer, Jr. A miniature, direct reading Velometer—4 in. high, 3 in. wide, 1- $\frac{1}{4}$ in. deep. Weight, 8 oz. Accurate, strong. Available in single and double scale ranges: 0-200 to 0-2500 fpm. Bulletin 725.



Alnor Thermo-Anemometer. For accurate measurement of low air velocity. Compact, direct-reading, battery operated, self-contained, portable. Scale 6 in. Meter ranges: 0-600 fpm and double range 0-300/100-2000 fpm. Accurate readings as low as 5 fpm. Temporary Bulletin 913-A.