Section 3 - HAZARDS IDENTIFICATION

Note: Avoid creating dust. The parts are not inherently hazardous. The listed effects relate to dust residues on the parts or to dust generated in installation.

-Effects of Overexposure

Eyes: May cause transient irritation with no corneal injury likely if immediately removed by washing. Repeated or prolonged exposure to resin fumes or dust may cause eye irritation.

Skin: Dust may cause minor irritation upon single contact but is not appreciably absorbed. Repeated contact may cause sensitization and skin rash.

Inhalation: Do not inhale dust. If dust is generated, proper mask must be worn designed to keep inhaled asbestos fiber count under 0.2 fibers/cc.

Ingestion: Do not ingest. Irritant to gastrointestinal tract.

Section 4 - FIRST AID MEASURES

-Emergency and First Aid Procedures

Should not be necessary from a proper handling of these friction material products.

Section 5 - FIREFIGHTING MEASURES

Flash Point: Not Available

Extinguishing Media: N/A

Special Firefighting Precautions: None

Unusual Fire and Explosion Hazards: None

Section 6 - ENVIRONMENTAL RELEASE MEASURES

-Steps to be taken in case material is released or spilled

No special procedures are required for solid parts. Follow the "Recommended Procedures" on page 5.