



Revised 2/14/86

MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910, 1200.
Standard must be consulted for specific requirements.

The product identity on this page meets the OSHA definition of an article and is exempt from the Hazard Communication Standard as to all normally careful uses. Some potential may exist for exposure to dust.

The ingredients in these products are resin-bonded and hazards normally associated with contact to pure dusts of the listed ingredients should not be significant. Abex has listed all of the essential ingredients present in a series of products of this general description. All products identified on this MSDS contain asbestos-free material but will not contain all of the other materials shown. The recommended exposure limits are those for the most hazardous substance in a class of substances. Exact formulation is considered proprietary and confidential. Precise product information will not be disclosed, other than to a health professional in accordance with the regulations, without an approved Secrecy Agreement.

The information herein is believed to be accurate, however, Abex makes no representation or warranty as to its accuracy. This data is furnished gratuitously and independently of any sale of the product, and only for customer investigation and independent verification.

Abex shall in no event be responsible for any damages of whatever nature directly or indirectly resulting from the publication or use of or reliance upon data contained herein. No express or implied warranty of any kind, including warranties of merchantability or fitness for use, with respect to the product or to the data herein is made hereunder.

IDENTITY (As Used on Label and List)

1047-47

931-86, 83, 162&182A), 987-6, 3027-(73,85&88), 303-67, 3041-29, ABEX (647GG, 697EE, 685FF, 6009FF, 6000GG, 6008FF, 6014FF, 6011FF), ABB (281GG, 294EE, 282FF, 296GG, 2003FF, 2010FF, 2007FF, 2005FF), COM (371GG, 383EE, 372FF, 395FF, 385GG, 382FF, 3000FF, 397FF), ABEX 6012FF, ABB208FF, COM398FF, NA27, NA27R, ABEX 6020FF, ABB2015FF, COM3005FF, 3030-67

SECTION I

Manufacturer's Name: **ABEX CORPORATION**
Friction Products Division

Emergency Telephone Number (703) 662-3842

Telephone Number for Information (703) 662-3871

Address: (Number, Street, City, State, Zip Code)

2410 Papermill Road, P.O. Box 3250
Winchester, VA. 22601

Date Prepared November 12, 1985

Preparer M. K. Leung

SECTION II - Hazardous Ingredients/Identity Information**Hazardous Components**

(Specific Chemical Identity: Common Name(s))

OSHA PEL ACGIH TLV

Glass Fiber	10.0 mg/M ³	10.0 mg/M ³
Silica, Silicate, Tripoli, Talc	0.1 mg/M ³	0.1 mg/M ³
Carbon Black, Graphite, Coal, Coke	2.0 mg/M ³	2.0 mg/M ³
Phenolic and Cashew Compounds	5.0 mg/M ³	5.0 mg/M ³
Wood Flour and Other Fillers	1.0 mg/M ³	1.0 mg/M ³
Iron, Zinc, Aluminum, Brass and their Oxides	10.0 mg/M ³	10.0 mg/M ³

SECTION III - Physical / Chemical Characteristics

Boiling Point	NA	Specific Gravity (H ₂ O - 1)	1.5 - 3.5
Vapor Pressure (mm Hg.)	NA	Melting Point	NA
Vapor Density (Air - 1)	NA	Evaporation Rate (Butyl Acetate - 1)	0
Solubility in Water	No		
Appearance and Odor	Solid, Odor, Dark Grey Color		Warner SBC-25-000036

Form #4

cc: G. FEINSTEIN, J. HANSEN / 10/22 4/8/86

SCF-ABEX-2886