

VCM EXPOSURE TRAINING

-TEST, 1982-

PETE MARKEY
NAME

VINYL
DEPARTMENT

9/18/82
DATE

1. Evidence has been found that exposure to high-level concentrations of VCM over long periods of time could cause cancer of the liver.
True(☒) False(☐)
2. A finger bone disease, acraosteolysis ("AOL"), has been linked to the manual cleaning of PVC reactors.
True(☒) False(☐)
3. Liquid VCM can cause severe frostbite.
True(☒) False(☐)
4. The exposure limits for VCM are 1 ppm average for any eight hour period and 10 ppm for any 15 minute period.
5. The three VCM regulated areas in the plant are:
 - A. Dry blend basement, Q.C. Lab and the Plasticizer Tank Farm.
 - B. Plasticizer Building, Boiler House and the East Warehouse.
 - ☒ C. VCM Tank Farm and the two large reactor areas.
6. If you have no business in a VCM regulated area, you must stay out.
True(☒) False(☐)
7. Respiratory equipment (gas mask, air-line respirators, Scott Air-Pack, etc.) is ~~required~~ above (but not below):
(A) 1.0 ppm (B) 0.5 ppm (C) 10.0 ppm
8. Our Honeywell continuous monitors alarm when 1 ppm is detected in an area.
9. We monitor your VCM exposure to:
 - A. Minimize your exposure to VCM.
 - B. Monitor progress in reducing VCM concentrations.
 - ☒ C. Both A & B.
 - D. To make sure we have a record.
10. Protective clothing is required for certain jobs.
True(☒) False(☐)

VCM EXPOSURE TRAINING

-TEST, 1980-

NAME

DEPARTMENT

DATE

Ronald A. Chisn

Construction

9-18-80

1. Evidence has been found that exposure to high-level concentrations of VCM over long periods of time could cause cancer of the liver.
True(☒) False(☐)
2. A finger bone disease, acraosteolysis ("AOL"), has been linked to the manual cleaning of PVC reactors.
True(☒) False(☐)
3. Liquid VCM can cause severe frostbite.
True(☒) False(☐)
4. The exposure limits for VCM are 1 ppm average for any eight hour period and 1,000 ppm for any 15 minute period.
5. The three VCM regulated areas in the plant are:
 - A. Dry blend basement, Q.C. Lab and the Plasticizer Tank Farm.
 - B. Plasticizer Building, Boiler House and the East Warehouse.
 - ☒ C. VCM Tank Farm and the two large reactor areas.
6. If you have no business in a VCM regulated area, you must stay out.
True(☒) False(☐)
7. Respiratory equipment (gas mask, air-line respirators, Scott Air-Pack, etc.) is required above (but not below):
☒ (A) 1.0 ppm (B) 0.5 ppm (C) 10.0 ppm
8. Our Honeywell continuous monitors alarm when 1 ppm is detected in an area.
9. We monitor your VCM exposure to:
 - A. Minimize your exposure to VCM.
 - B. Monitor progress in reducing VCM concentrations.
 - ☒ C. Both A & B.
 - D. To make sure we have a record.
10. Protective clothing is required for certain jobs.
True(☒) False(☐)

Ronald A. Chism

NAME

Warehouseman

DEPARTMENT

9-18-80

DATE

1. Excessive amounts of lead in the body can cause serious harm, including death.

True

X

False

The lead materials we have in this plant are powders used as heat stabilizers and color pigments in PVC compounds.

True

X

False

3. The exposure limit for lead is 50 micrograms of lead per cubic meter of air for any eight-hour work period.

4. The exposure limit for lead is lowered if you work more than eight (8) hours during a work period.

True

X

False

5. Lead used in this plant can enter the body by:

- A. Inhaling
B. Swallowing
C. Absorbing through the skin
D. All of the above
E. A & B Only

6. If you get lead material on your skin or clothing, you don't have to do anything about it because lead is not absorbed through your skin.

True

False

X

NOTE: If you think that was a "trick" question, you should think about your answer again.

7. Some lead tasks require breathing protection. Name one such task.

Samples in weigh room

8. It is O.K. to take food, drinks, etc. into lead areas, provided you are careful to not let lead materials get into them.

True

False

X

9. Medical testing is used to make certain your lead exposure is not hurting you.

True

X

False

10. If the lead area ventilation systems are working and your medical tests and monitoring results are all "Good," you don't have to be concerned.

True

False

X

If you're not sure about your answer, you need to think about it more.

NAME PETE MARKEY

DEPARTMENT VINYL

DATE 9/18/87

1. Excessive amounts of lead in the body can cause serious harm, including death.

True ☒

False ☐

2. The lead materials we have in this plant are powders used as heat stabilizers and color pigments in PVC compounds.

True ☒

False ☐

3. The exposure limit for lead is 50 micrograms of lead per cubic meter of air for any eight-hour work period.

4. The exposure limit for lead is lowered if you work more than eight (8) hours during a work period.

True ☒

False ☐

5. Lead used in this plant can enter the body by:

- A. Inhaling
- B. Swallowing
- C. Absorbing through the skin
- D. All of the above
- ☒ E. A & B Only

6. If you get lead material on your skin or clothing, you don't have to do anything about it because lead is not absorbed through your skin.

True ☐

False ☒

NOTE: If you think that was a "trick" question, you should think about your answer again.

7. Some lead tasks require breathing protection. Name one such task.

Weighing Lead Stabilizers in C.I.- weigh room

8. It is O.K. to take food, drinks, etc. into lead areas, provided you are careful to not let lead materials get into them.

True ☐

False ☒

9. Medical testing is used to make certain your lead exposure is not hurting you.

True ☒

False ☐

10. If the lead area ventilation systems are working and your medical tests and monitoring results are all "Good," you don't have to be concerned about lead exposure.

True ☐

False ☒

NOTE: If you're not sure about your answer, you need to think about it more.

RONALD CHISOM

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION I QUIZ

9-18-80

-
- True 1. Good, competent, professional forklift operation is a safe operation and you can never be too experienced to learn more about safety.
- True 2. The first rule of safe forklift operation is to know the capacity of your truck.
- True 3. The load capacity of each of our forklift trucks is clearly marked on the identification plate on the truck.
- False 4. If you are in doubt about your forklift's ability to pick up a certain load, use the trial and error approach.
- True 5. A pre-work check of your forklift should be made to be sure it's working right and will operate safely.
- False 6. The further the center of the load is away from the front of the carriage, the larger the load you can pick up.
- True 7. All of the forklift trucks in the Aberdeen Plant are equipped with a hand brake.
- False 8. You should try to repair any problems you find during the pre-work check of the forklift truck.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION II QUIZ

- T 1. A forklift truck steers with its rear wheels, not its front wheels like your car.
- F 2. When you are planning to make a turn while traveling forward, you should steer your forklift to the opposite side of the road or isle...in the direction you are going to turn.
- T 3. When traveling backward, the rear wheels should pass the corner and the front wheels should reach the corner before you start turning the steering wheel to make a turn.
- T 4. A forklift truck operator must always watch the rear swing of the truck as well as the front swing of the load.
- F 5. A forklift truck is much harder to steer when the forks are loaded.
- T 6. A forklift truck operator should always travel with the forks four to six inches above the ground.
- T 7. An operator should always inspect a load before he attempts to make a lift.
- T 8. When picking up a load with a forklift truck, always approach the load squarely.
- T 9. The forks should be spaced as widely as possible according to the load width and equally spaced from the sides of the carriage.
- F 10. At times, it might become necessary to make a lift with only one fork.
- F 11. At times, it might also become necessary to "pick up short", that is pick up a load with only part of your forks.
- T 12. An operator should never put his head, hands or feet out of the truck cage.
- T 13. Only the small Hyster forklift should ever be carried in the plant's elevators.
- F 14. It is better to drive forward up a ramp when your truck is empty.
- T 15. You should drive forward up a ramp and backwards down a ramp when your forks are loaded.

- Page 2 -
SECTION II QUIZ

- I 16. Always cross railroad tracks at a 45 degree angle.
- I 17. Passengers should never be carried on a forklift truck as it is designed for only one person...the operator.
- I 18. Before depositing a load, the operator should take the time to inspect the place where he is going to unload.
- I 19. You should never use full back tilt when high stacking. The safest condition is when the top of the mast is only a foot to 18 inches back from vertical.
- I 20. If you have to leave the fork truck unattended for even a short time, you should lower the forks and turn off the engine.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION III QUIZ

-
- T 1. If the tractor is attached to the trailer, you should be sure to notify the driver that you are about to begin loading the trailer.
- F 2. It is not necessary to chock the wheels of a trailer to be loaded if the tractor is attached.
- T 3. In addition to the dolly wheels, special jacks must be placed under the front of a trailer, when the tractor is not attached, before loading begins.
- T 4. Trailer floors should be checked for damage before loading begins.
- F 5. The proper way to load a trailer is to load all of one side then all of the other side.
- T 6. If double stacking is required when loading a trailer, it should be done in the front and back so the extra weight will be on the axles.
- T 7. An employee should never be lifted with a forklift truck unless a caged worklift is used.
- T 8. When using a worklift, you must be sure that the safety pin is placed through the worklift mount and the forklift forks to prevent the worklift from sliding off the forks.
- F 9. It is O.K. for an employee to ride to a work site if he is riding in a worklift.
- T 10. Unloading a trash dumpster should be done with forklift mast straight up, not tilted forward or backward.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION I QUIZ

- 9-18-80
-
- T 1. Good, competent, professional forklift operation is a safe operation and you can never be too experienced to learn more about safety.
- T 2. The first rule of safe forklift operation is to know the capacity of your truck.
- T 3. The load capacity of each of our forklift trucks is clearly marked on the identification plate on the truck.
- F 4. If you are in doubt about your forklift's ability to pick up a certain load, use the trial and error approach.
- T 5. A pre-work check of your forklift should be made to be sure it's working right and will operate safely.
- F 6. The further the center of the load is away from the front of the carriage, the larger the load you can pick up.
- T 7. All of the forklift trucks in the Aberdeen Plant are equipped with a hand brake.
- F 8. You should try to repair any problems you find during the pre-work check of the forklift truck.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION II QUIZ

- T 1. A forklift truck steers with its rear wheels, not its front wheels like your car.
- F 2. When you are planning to make a turn while traveling forward, you should steer your forklift to the opposite side of the road or isle...in the direction you are going to turn.
- T 3. When traveling backward, the rear wheels should pass the corner and the front wheels should reach the corner before you start turning the steering wheel to make a turn.
- T 4. A forklift truck operator must always watch the rear swing of the truck as well as the front swing of the load.
- F 5. A forklift truck is much harder to steer when the forks are loaded.
- T 6. A forklift truck operator should always travel with the forks four to six inches above the ground.
- T 7. An operator should always inspect a load before he attempts to make a lift.
- T 8. When picking up a load with a forklift truck, always approach the load squarely.
- T 9. The forks should be spaced as widely as possible according to the load width and equally spaced from the sides of the carriage.
- F 10. At times, it might become necessary to make a lift with only one fork.
- F 11. At times, it might also become necessary to "pick up short", that is pick up a load with only part of your forks.
- T 12. An operator should never put his head, hands or feet out of the truck cage.
- T 13. Only the small Hyster forklift should ever be carried in the plant's elevators.
- F 14. It is better to drive forward up a ramp when your truck is empty.
- T 15. You should drive forward up a ramp and backwards down a ramp when your forks are loaded.

- Page 2 -
SECTION II QUIZ

- T 16. Always cross railroad tracks at a 45 degree angle.
- T 17. Passengers should never be carried on a forklift truck as it is designed for only one person...the operator.
- T 18. Before depositing a load, the operator should take the time to inspect the place where he is going to unload.
- T 19. You should never use full back tilt when high stacking. The safest condition is when the top of the mast is only a foot to 18 inches back from vertical.
- T 20. If you have to leave the fork truck unattended for even a short time, you should lower the forks and turn off the engine.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION III QUIZ

-
- T 1. If the tractor is attached to the trailer, you should be sure to notify the driver that you are about to begin loading the trailer.
- F 2. It is not necessary to chock the wheels of a trailer to be loaded if the tractor is attached.
- T 3. In addition to the dolly wheels, special jacks must be placed under the front of a trailer, when the tractor is not attached, before loading begins.
- T 4. Trailer floors should be checked for damage before loading begins.
- F 5. The proper way to load a trailer is to load all of one side then all of the other side.
- T 6. If double stacking is required when loading a trailer, it should be done in the front and back so the extra weight will be on the axles.
- T 7. An employee should never be lifted with a forklift truck unless a caged worklift is used.
- T 8. When using a worklift, you must be sure that the safety pin is placed through the worklift mount and the forklift forks to prevent the worklift from sliding off the forks.
- F 9. It is O.K. for an employee to ride to a work site if he is riding in a worklift.
- T 10. Unloading a trash dumpster should be done with forklift mast straight up, not tilted forward or backward.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION III QUIZ

HEARD WILLIE C

- T 1. If the tractor is attached to the trailer, you should be sure to notify the driver that you are about to begin loading the trailer.
- ✓ T 2. It is not necessary to chock the wheels of a trailer to be loaded if the tractor is attached.
- T 3. In addition to the dolly wheels, special jacks must be placed under the front of a trailer, when the tractor is not attached, before loading begins.
- T 4. Trailer floors should be checked for damage before loading begins.
- ✓ T 5. The proper way to load a trailer is to load all of one side then all of the other side.
- T 6. If double stacking is required when loading a trailer, it should be done in the front and back so the extra weight will be on the axles.
- T 7. An employee should never be lifted with a forklift truck unless a caged worklift is used.
- T 8. When using a worklift, you must be sure that the safety pin is placed through the worklift mount and the forklift forks to prevent the worklift from sliding off the forks.
- F 9. It is O.K. for an employee to ride to a work site if he is riding in a worklift.
- T 10. Unloading a trash dumpster should be done with forklift mast straight up, not tilted forward or backward.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION III QUIZ

Ricky Lee

-
- T 1. If the tractor is attached to the trailer, you should be sure to notify the driver that you are about to begin loading the trailer.
- F 2. It is not necessary to chock the wheels of a trailer to be loaded if the tractor is attached.
- T 3. In addition to the dolly wheels, special jacks must be placed under the front of a trailer, when the tractor is not attached, before loading begins.
- T 4. Trailer floors should be checked for damage before loading begins.
- F 5. The proper way to load a trailer is to load all of one side then all of the other side.
- T 6. If double stacking is required when loading a trailer, it should be done in the front and back so the extra weight will be on the axles.
- T 7. An employee should never be lifted with a forklift truck unless a caged worklift is used.
- T 8. When using a worklift, you must be sure that the safety pin is placed through the worklift mount and the forklift forks to prevent the worklift from sliding off the forks.
- F 9. It is O.K. for an employee to ride to a work site if he is riding in a worklift.
- T 10. Unloading a trash dumpster should be done with forklift mast straight up, not tilted forward or backward.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION III QUIZ

Bobby Joe Zimble

- T 1. If the tractor is attached to the trailer, you should be sure to notify the driver that you are about to begin loading the trailer.
- F 2. It is not necessary to chock the wheels of a trailer to be loaded if the tractor is attached.
- T 3. In addition to the dolly wheels, special jacks must be placed under the front of a trailer, when the tractor is not attached, before loading begins.
- T 4. Trailer floors should be checked for damage before loading begins.
- F 5. The proper way to load a trailer is to load all of one side then all of the other side.
- T 6. If double stacking is required when loading a trailer, it should be done in the front and back so the extra weight will be on the axles.
- T 7. An employee should never be lifted with a forklift truck unless a caged worklift is used.
- T 8. When using a worklift, you must be sure that the safety pin is placed through the worklift mount and the forklift forks to prevent the worklift from sliding off the forks.
- F 9. It is O.K. for an employee to ride to a work site if he is riding in a worklift.
- T 10. Unloading a trash dumpster should be done with forklift mast straight up, not tilted forward or backward.

ABERDEEN FORKLIFT TRAINING PROGRAM

HEARDVILLE SECTION II QUIZ

- T 1. A forklift truck steers with its rear wheels, not its front wheels like your car.
- T 2. When you are planning to make a turn while traveling forward, you should steer your forklift to the opposite side of the road or isle...in the direction you are going to turn.
- T 3. When traveling backward, the rear wheels should pass the corner and the front wheels should reach the corner before you start turning the steering wheel to make a turn.
- T 4. A forklift truck operator must always watch the rear swing of the truck as well as the front swing of the load.
5. A forklift truck is much harder to steer when the forks are loaded.
- T 6. A forklift truck operator should always travel with the forks four to six inches above the ground.
- T 7. An operator should always inspect a load before he attempts to make a lift.
- T 8. When picking up a load with a forklift truck, always approach the load squarely.
- T 9. The forks should be spaced as widely as possible according to the load width and equally spaced from the sides of the carriage.
- F 10. At times, it might become necessary to make a lift with only one fork.
- F 11. At times, it might also become necessary to "pick up short", that is pick up a load with only part of your forks.
- T 12. An operator should never put his head, hands or feet out of the truck cage.
13. Only the small Hyster forklift should ever be carried in the plant's elevators.
- T 14. It is better to drive forward up a ramp when your truck is empty.
- T 15. You should drive forward up a ramp and backwards down a ramp when your forks are loaded.

- Page 2 -
SECTION II QUIZ

- T 16. Always cross railroad tracks at a 45 degree angle.
- T 17. Passengers should never be carried on a forklift truck as it is designed for only one person...the operator.
- T 18. Before depositing a load, the operator should take the time to inspect the place where he is going to unload.
- 19. You should never use full back tilt when high stacking. The safest condition is when the top of the mast is only a foot to 18 inches back from vertical.
- T 20. If you have to leave the fork truck unattended for even a short time, you should lower the forks and turn off the engine.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION II QUIZ

Rishy Rea

- T 1. A forklift truck steers with its rear wheels, not its front wheels like your car.
- F 2. When you are planning to make a turn while traveling forward, you should steer your forklift to the opposite side of the road or isle...in the direction you are going to turn.
- T 3. When traveling backward, the rear wheels should pass the corner and the front wheels should reach the corner before you start turning the steering wheel to make a turn.
- T 4. A forklift truck operator must always watch the rear swing of the truck as well as the front swing of the load.
- F 5. A forklift truck is much harder to steer when the forks are loaded.
- T 6. A forklift truck operator should always travel with the forks four to six inches above the ground.
- T 7. An operator should always inspect a load before he attempts to make a lift.
- T 8. When picking up a load with a forklift truck, always approach the load squarely.
- T 9. The forks should be spaced as widely as possible according to the load width and equally spaced from the sides of the carriage.
- F 10. At times, it might become necessary to make a lift with only one fork.
- F 11. At times, it might also become necessary to "pick up short", that is pick up a load with only part of your forks.
- T 12. An operator should never put his head, hands or feet out of the truck cage.
- T 13. Only the small Hyster forklift should ever be carried in the plant's elevators.
- F 14. It is better to drive forward up a ramp when your truck is empty.
- T 15. You should drive forward up a ramp and backwards down a ramp when your forks are loaded.

- Page 2 -
SECTION II QUIZ

- / 16. Always cross railroad tracks at a 45 degree angle.
- / 17. Passengers should never be carried on a forklift truck as it is designed for only one person...the operator.
- / 18. Before depositing a load, the operator should take the time to inspect the place where he is going to unload.
- / 19. You should never use full back tilt when high stacking. The safest condition is when the top of the mast is only a foot to 18 inches back from vertical.
- / 20. If you have to leave the fork truck unattended for even a short time, you should lower the forks and turn off the engine.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION II QUIZ

Bobby Joe Trimble

- T 1. A forklift truck steers with its rear wheels, not its front wheels like your car.
- T 2. When you are planning to make a turn while traveling forward, you should steer your forklift to the opposite side of the road or isle...in the direction you are going to turn.
- T 3. When traveling backward, the rear wheels should pass the corner and the front wheels should reach the corner before you start turning the steering wheel to make a turn.
- T 4. A forklift truck operator must always watch the rear swing of the truck as well as the front swing of the load.
- F 5. A forklift truck is much harder to steer when the forks are loaded.
- T 6. A forklift truck operator should always travel with the forks four to six inches above the ground.
- T 7. An operator should always inspect a load before he attempts to make a lift.
- T 8. When picking up a load with a forklift truck, always approach the load squarely.
- T 9. The forks should be spaced as widely as possible according to the load width and equally spaced from the sides of the carriage.
- F 10. At times, it might become necessary to make a lift with only one fork.
- F 11. At times, it might also become necessary to "pick up short", that is pick up a load with only part of your forks.
- T 12. An operator should never put his head, hands or feet out of the truck cage.
- T 13. Only the small Hyster forklift should ever be carried in the plant's elevators.
- F 14. It is better to drive forward up a ramp when your truck is empty.
- T 15. You should drive forward up a ramp and backwards down a ramp when your forks are loaded.

- Page 2 -
SECTION II QUIZ

- T 16. Always cross railroad tracks at a 45 degree angle.
- T 17. Passengers should never be carried on a forklift truck as it is designed for only one person...the operator.
- T 18. Before depositing a load, the operator should take the time to inspect the place where he is going to unload.
- T 19. You should never use full back tilt when high stacking. The safest condition is when the top of the mast is only a foot to 18 inches back from vertical.
- T 20. If you have to leave the fork truck unattended for even a short time, you should lower the forks and turn off the engine.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION 1 QUIZ

Ricky Rm

- T 1. Good, competent, professional forklift operation is a safe operation and you can never be too experienced to learn more about safety.
- T 2. The first rule of safe forklift operation is to know the capacity of your truck.
- T 3. The load capacity of each of our forklift trucks is clearly marked on the identification plate on the truck.
- T 4. If you are in doubt about your forklift's ability to pick up a certain load, use the trial and error approach.
- T 5. A pre-work check of your forklift should be made to be sure it's working right and will operate safely.
- F 6. The further the center of the load is away from the front of the carriage, the larger the load you can pick up.
- F 7. All of the forklift trucks in the Aberdeen Plant are equipped with a hand brake.
- F 8. You should try to repair any problems you find during the pre-work check of the forklift truck.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION I QUIZ

Willie H. [signature]

- TRUE 1. Good, competent, professional forklift operation is a safe operation and you can never be too experienced to learn more about safety.
- TRUE 2. The first rule of safe forklift operation is to know the capacity of your truck.
- TRUE 3. The load capacity of each of our forklift trucks is clearly marked on the identification plate on the truck.
- FALSE 4. If you are in doubt about your forklift's ability to pick up a certain load, use the trial and error approach.
- TRUE 5. A pre-work check of your forklift should be made to be sure it's working right and will operate safely.
- FALSE 6. The further the center of the load is away from the front of the carriage, the larger the load you can pick up.
- TRUE 7. All of the forklift trucks in the Aberdeen Plant are equipped with a hand brake.
- FALSE 8. You should try to repair any problems you find during the pre-work check of the forklift truck.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION I QUIZ

Bobby Joe Trimble

-
- T 1. Good, competent, professional forklift operation is a safe operation and you can never be too experienced to learn more about safety.
- T 2. The first rule of safe forklift operation is to know the capacity of your truck.
- T 3. The load capacity of each of our forklift trucks is clearly marked on the identification plate on the truck.
- F 4. If you are in doubt about your forklift's ability to pick up a certain load, use the trial and error approach.
- T 5. A pre-work check of your forklift should be made to be sure it's working right and will operate safely.
- F 6. The further the center of the load is away from the front of the carriage, the larger the load you can pick up.
- F 7. All of the forklift trucks in the Aberdeen Plant are equipped with a hand brake.
- T 8. You should try to repair any problems you find during the pre-work check of the forklift truck.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION III QUIZ

-
- True 1. If the tractor is attached to the trailer, you should be sure to notify the driver that you are about to begin loading the trailer.
- False 2. It is not necessary to chock the wheels of a trailer to be loaded if the tractor is attached.
- True 3. In addition to the dolly wheels, special jacks must be placed under the front of a trailer, when the tractor is not attached, before loading begins.
- True 4. Trailer floors should be checked for damage before loading begins.
- False 5. The proper way to load a trailer is to load all of one side then all of the other side.
- True 6. If double stacking is required when loading a trailer, it should be done in the front and back so the extra weight will be on the axles.
- True 7. An employee should never be lifted with a forklift truck unless a caged worklift is used.
- True 8. When using a worklift, you must be sure that the safety pin is placed through the worklift mount and the forklift forks to prevent the worklift from sliding off the forks.
- False 9. It is O.K. for an employee to ride to a work site if he is riding in a worklift.
- True 10. Unloading a trash dumpster should be done with forklift mast straight up, not tilted forward or backward.

ABERDEEN FORKLIFT TRAINING PROGRAM

100

SECTION I QUIZ

Aaron Dobson, Jr

- ✓ T 1. Good, competent, professional forklift operation is a safe operation and you can never be too experienced to learn more about safety.
- ✓ T 2. The first rule of safe forklift operation is to know the capacity of your truck.
- ✓ T 3. The load capacity of each of our forklift trucks is clearly marked on the identification plate on the truck.
- ✓ F 4. If you are in doubt about your forklift's ability to pick up a certain load, use the trial and error approach.
- ✓ T 5. A pre-work check of your forklift should be made to be sure it's working right and will operate safely.
- ✓ F 6. The further the center of the load is away from the front of the carriage, the larger the load you can pick up.
- ✓ F 7. All of the forklift trucks in the Aberdeen Plant are equipped with a hand brake.
- ✓ F 8. You should try to repair any problems you find during the pre-work check of the forklift truck.

ABERDEEN FORKLIFT TRAINING PROGRAM

95

AARON DEBSON, JR. SECTION II QUIZ

- ✓ T 1. A forklift truck steers with its rear wheels, not its front wheels like your car.
- ✓ F 2. When you are planning to make a turn while traveling forward, you should steer your forklift to the opposite side of the road or isle...in the direction you are going to turn.
- ✓ T 3. When traveling backward, the rear wheels should pass the corner and the front wheels should reach the corner before you start turning the steering wheel to make a turn.
- ✓ T 4. A forklift truck operator must always watch the rear swing of the truck as well as the front swing of the load.
- ✓ F 5. A forklift truck is much harder to steer when the forks are loaded.
- ✓ T 6. A forklift truck operator should always travel with the forks four to six inches above the ground.
- ✓ T 7. An operator should always inspect a load before he attempts to make a lift.
- ✓ T 8. When picking up a load with a forklift truck, always approach the load squarely.
- ✓ T 9. The forks should be spaced as widely as possible according to the load width and equally spaced from the sides of the carriage.
- ✓ F 10. At times, it might become necessary to make a lift with only one fork.
- ✓ F 11. At times, it might also become necessary to "pick up short", that is pick up a load with only part of your forks.
- ✓ T 12. An operator should never put his head, hands or feet out of the truck cage.
- ✓ T 13. Only the small Hyster forklift should ever be carried in the plant's elevators.
- ✓ F 14. It is better to drive forward up a ramp when your truck is empty.
- ✓ F 15. You should drive forward up a ramp and backwards down a ramp when your forks are loaded.

- Page 2 -
SECTION II QUIZ

- ✓ T 16. Always cross railroad tracks at a 45 degree angle.
- ✓ T 17. Passengers should never be carried on a forklift truck as it is designed for only one person...the operator.
- ✓ T 18. Before depositing a load, the operator should take the time to inspect the place where he is going to unload.
- ✓ T 19. You should never use full back tilt when high stacking. The safest condition is when the top of the mast is only a foot to 18 inches back from vertical.
- ✓ T 20. If you have to leave the fork truck unattended for even a short time, you should lower the forks and turn off the engine.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION III QUIZ

Aaron Dobson, Jr.

- T 1. If the tractor is attached to the trailer, you should be sure to notify the driver that you are about to begin loading the trailer.
- F 2. It is not necessary to chock the wheels of a trailer to be loaded if the tractor is attached.
- T 3. In addition to the dolly wheels, special jacks must be placed under the front of a trailer, when the tractor is not attached, before loading begins.
- T 4. Trailer floors should be checked for damage before loading begins.
- F 5. The proper way to load a trailer is to load all of one side then all of the other side.
- T 6. If double stacking is required when loading a trailer, it should be done in the front and back so the extra weight will be on the axles.
- T 7. An employee should never be lifted with a forklift truck unless a caged worklift is used.
- T 8. When using a worklift, you must be sure that the safety pin is placed through the worklift mount and the forklift forks to prevent the worklift from sliding off the forks.
- F 9. It is O.K. for an employee to ride to a work site if he is riding in a worklift.
- T 10. Unloading a trash dumpster should be done with forklift mast straight up, not tilted forward or backward.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION II QUIZ

- T 1. A forklift truck steers with its rear wheels, not its front wheels like your car.
- T 2. When you are planning to make a turn while traveling forward, you should steer your forklift to the opposite side of the road or isle...in the direction you are going to turn.
- T 3. When traveling backward, the rear wheels should pass the corner and the front wheels should reach the corner before you start turning the steering wheel to make a turn.
- T 4. A forklift truck operator must always watch the rear swing of the truck as well as the front swing of the load.
- F 5. A forklift truck is much harder to steer when the forks are loaded.
- T 6. A forklift truck operator should always travel with the forks four to six inches above the ground.
- T 7. An operator should always inspect a load before he attempts to make a lift.
- T 8. When picking up a load with a forklift truck, always approach the load squarely.
- T 9. The forks should be spaced as widely as possible according to the load width and equally spaced from the sides of the carriage.
- F 10. At times, it might become necessary to make a lift with only one fork.
- F 11. At times, it might also become necessary to "pick up short", that is pick up a load with only part of your forks.
- T 12. An operator should never put his head, hands or feet out of the truck cage.
- T 13. Only the small Hyster forklift should ever be carried in the plant's elevators.
- F 14. It is better to drive forward up a ramp when your truck is empty.
- T 15. You should drive forward up a ramp and backwards down a ramp when your forks are loaded.

- Page 2 -
SECTION II QUIZ

- T 16. Always cross railroad tracks at a 45 degree angle.
- T 17. Passengers should never be carried on a forklift truck as it is designed for only one person...the operator.
- T 18. Before depositing a load, the operator should take the time to inspect the place where he is going to unload.
- T 19. You should never use full back tilt when high stacking. The safest condition is when the top of the mast is only a foot to 18 inches back from vertical.
- T 20. If you have to leave the fork truck unattended for even a short time, you should lower the forks and turn off the engine.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION I QUIZ

-
- T 1. Good, competent, professional forklift operation is a safe operation and you can never be too experienced to learn more about safety.
- T 2. The first rule of safe forklift operation is to know the capacity of your truck.
- T 3. The load capacity of each of our forklift trucks is clearly marked on the identification plate on the truck.
- F 4. If you are in doubt about your forklift's ability to pick up a certain load, use the trial and error approach.
- T 5. A pre-work check of your forklift should be made to be sure it's working right and will operate safely.
- F 6. The further the center of the load is away from the front of the carriage, the larger the load you can pick up.
- F 7. All of the forklift trucks in the Aberdeen Plant are equipped with a hand brake.
- F 8. You should try to repair any problems you find during the pre-work check of the forklift truck.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION I QUIZ

Mark Chyter

- True* 1. Good, competent, professional forklift operation is a safe operation and you can never be too experienced to learn more about safety.
- True* 2. The first rule of safe forklift operation is to know the capacity of your truck.
- True* 3. The load capacity of each of our forklift trucks is clearly marked on the identification plate on the truck.
- False* 4. If you are in doubt about your forklift's ability to pick up a certain load, use the trial and error approach.
- True* 5. A pre-work check of your forklift should be made to be sure it's working right and will operate safely.
- False* 6. The further the center of the load is away from the front of the carriage, the larger the load you can pick up.
- False* 7. All of the forklift trucks in the Aberdeen Plant are equipped with a hand brake.
- True* 8. You should try to repair any problems you find during the pre-work check of the forklift truck.

ABERDEEN FORKLIFT TRAINING PROGRAM

90

Michael P. Clapton SECTION II QUIZ

- T 1. A forklift truck steers with its rear wheels, not its front wheels like your car.
- F 2. When you are planning to make a turn while traveling forward, you should steer your forklift to the opposite side of the road or isle...in the direction you are going to turn.
- T 3. When traveling backward, the rear wheels should pass the corner and the front wheels should reach the corner before you start turning the steering wheel to make a turn.
- T 4. A forklift truck operator must always watch the rear swing of the truck as well as the front swing of the load.
- F 5. A forklift truck is much harder to steer when the forks are loaded.
- T 6. A forklift truck operator should always travel with the forks four to six inches above the ground.
- T 7. An operator should always inspect a load before he attempts to make a lift.
- T 8. When picking up a load with a forklift truck, always approach the load squarely.
- T 9. The forks should be spaced as widely as possible according to the load width and equally spaced from the sides of the carriage.
- F 10. At times, it might become necessary to make a lift with only one fork.
- F 11. At times, it might also become necessary to "pick up short", that is pick up a load with only part of your forks.
- T 12. An operator should never put his head, hands or feet out of the truck cage.
- T 13. Only the small Hyster forklift should ever be carried in the plant's elevators.
- T 14. It is better to drive forward up a ramp when your truck is empty.
- F 15. You should drive forward up a ramp and backwards down a ramp when your forks are loaded.

- Page 2 -
SECTION II QUIZ

A

- ☒ 16. Always cross railroad tracks at a 45 degree angle.
- ☒ 17. Passengers should never be carried on a forklift truck as it is designed for only one person...the operator.
- ☒ 18. Before depositing a load, the operator should take the time to inspect the place where he is going to unload.
- ☒ 19. You should never use full back tilt when high stacking. The safest condition is when the top of the mast is only a foot to 18 inches back from vertical.
- ☒ 20. If you have to leave the fork truck unattended for even a short time, you should lower the forks and turn off the engine.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION III QUIZ

Michael J. Closter

- T 1. If the tractor is attached to the trailer, you should be sure to notify the driver that you are about to begin loading the trailer.
- F 2. It is not necessary to chock the wheels of a trailer to be loaded if the tractor is attached.
- T 3. In addition to the dolly wheels, special jacks must be placed under the front of a trailer, when the tractor is not attached, before loading begins.
- T 4. Trailer floors should be checked for damage before loading begins.
- F 5. The proper way to load a trailer is to load all of one side then all of the other side.
- T 6. If double stacking is required when loading a trailer, it should be done in the front and back so the extra weight will be on the axles.
- T 7. An employee should never be lifted with a forklift truck unless a caged worklift is used.
- T 8. When using a worklift, you must be sure that the safety pin is placed through the worklift mount and the forklift forks to prevent the worklift from sliding off the forks.
- F 9. It is O.K. for an employee to ride to a work site if he is riding in a worklift.
- T 10. Unloading a trash dumpster should be done with forklift mast straight up, not tilted forward or backward.

100

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION I QUIZ

Bill Caldwell Vinyl 1/18/80

- True 1. Good, competent, professional forklift operation is a safe operation and you can never be too experienced to learn more about safety.
- True 2. The first rule of safe forklift operation is to know the capacity of your truck.
- True 3. The load capacity of each of our forklift trucks is clearly marked on the identification plate on the truck.
- False 4. If you are in doubt about your forklift's ability to pick up a certain load, use the trial and error approach.
- True 5. A pre-work check of your forklift should be made to be sure it's working right and will operate safely.
- False 6. The further the center of the load is away from the front of the carriage, the larger the load you can pick up.
- False 7. All of the forklift trucks in the Aberdeen Plant are equipped with a hand brake.
- False 8. You should try to repair any problems you find during the pre-work check of the forklift truck.

- Page 2 -
SECTION II QUIZ

- T 16. Always cross railroad tracks at a 45 degree angle.
- T 17. Passengers should never be carried on a forklift truck as it is designed for only one person...the operator.
- T 18. Before depositing a load, the operator should take the time to inspect the place where he is going to unload.
- T 19. You should never use full back tilt when high stacking. The safest condition is when the top of the mast is only a foot to 18 inches back from vertical.
- T 20. If you have to leave the fork truck unattended for even a short time, you should lower the forks and turn off the engine.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION I QUIZ

Vernito Peters Vainly Jan 24-80

- True 1. Good, competent, professional forklift operation is a safe operation and you can never be too experienced to learn more about safety.
- True 2. The first rule of safe forklift operation is to know the capacity of your truck.
- True 3. The load capacity of each of our forklift trucks is clearly marked on the identification plate on the truck.
- True 4. If you are in doubt about your forklift's ability to pick up a certain load, use the trial and error approach.
- True 5. A pre-work check of your forklift should be made to be sure it's working right and will operate safely.
- False 6. The further the center of the load is away from the front of the carriage, the larger the load you can pick up.
- False 7. All of the forklift trucks in the Aberdeen Plant are equipped with a hand brake.
- False 8. You should try to repair any problems you find during the pre-work check of the forklift truck.

100

A

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION I QUIZ

MIKE MAYS

VingL

1-24-80

- True 1. Good, competent, professional forklift operation is a safe operation and you can never be too experienced to learn more about safety.
- True 2. The first rule of safe forklift operation is to know the capacity of your truck.
- True 3. The load capacity of each of our forklift trucks is clearly marked on the identification plate on the truck.
- False 4. If you are in doubt about your forklift's ability to pick up a certain load, use the trial and error approach.
- True 5. A pre-work check of your forklift should be made to be sure it's working right and will operate safely.
- False 6. The further the center of the load is away from the front of the carriage, the larger the load you can pick up.
- False 7. All of the forklift trucks in the Aberdeen Plant are equipped with a hand brake.
- False 8. You should try to repair any problems you find during the pre-work check of the forklift truck.

NAME

MIKE MAXS

DEPARTMENT

VINYL

DATE

1-24-80

1. Excessive amounts of lead in the body can cause serious harm, including death.

True

☒

False

☐

2. The lead materials we have in this plant are powders used as heat stabilizers and color pigments in PVC compounds.

True

☒

False

☐

3. The exposure limit for lead is 50 micrograms of lead per cubic meter of air for any eight-hour work period.

4. The exposure limit for lead is lowered if you work more than eight (8) hours during a work period.

True

☒

False

☐

5. Lead used in this plant can enter the body by:

- A. Inhaling
B. Swallowing
C. Absorbing through the skin
D. All of the above
☒ E. A & B Only

6. If you get lead material on your skin or clothing, you don't have to do anything about it because lead is not absorbed through your skin.

True

☐

False

☒

NOTE: If you think that was a "trick" question, you should think about your answer again.

7. Some lead tasks require breathing protection. Name one such task.

Dumping lead powder from bag into machine

8. It is O.K. to take food, drinks, etc. into lead areas, provided you are careful to not let lead materials get into them.

True

☐

False

☒

9. Medical testing is used to make certain your lead exposure is not hurting you.

True

☒

False

☐

10. If the lead area ventilation systems are working and your medical tests and monitoring results are all "Good," you don't have to be concerned about lead exposures.

True

☐

False

☒

NOTE: If you're not sure about your answer, you need to think about it some more.

VAB.0001076922

100

VCM EXPOSURE TRAINING

-TEST, 1979-

NAME

MIKE MAY

DEPARTMENT

VIA

DATE

1-24-1980

1. Evidence has been found that exposure to high-level concentrations of VCM over long periods of time could cause cancer of the liver.
True(~~X~~) False()
2. A finger bone disease, acraosteolysis ("AOL"), has been linked to the manual cleaning of PVC reactors.
True(~~X~~) False()
3. Liquid VCM can cause severe frostbite.
True(~~X~~) False()
4. The exposure limits for VCM are 1 ppm average for any eight hour period and 5 ppm for any 15 minute period.
5. The three VCM regulated areas in the plant are:
 - A. Dry blend basement, Q.C. Lab and the Plasticizer Tank Farm.
 - B. Plasticizer Building, Boiler House and the East Warehouse.
 - C VCM Tank Farm and the two large reactor areas.
6. If you have no business in a VCM regulated area, you must stay out.
True(~~X~~) False()
7. Respiratory equipment (gas mask, air-line respirators, Scott Air-Pack, etc.) is required above (but not below):
(A) 1.0 ppm (B) 0.5 ppm (C) 10.0 ppm
8. Our Honeywell continuous monitors alarm when above 1 ppm is detected in an area.
9. We monitor your VCM exposure to:
 - A. Minimize your exposure to VCM.
 - B. Monitor progress in reducing VCM concentrations.
 - C Both A & B.
 - D. To make sure we have a record.
10. Protective clothing is required for certain jobs.
True(~~X~~) False()

MIKE MAY'S Vinyl

1-24-80

A

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION II QUIZ

100

- TRUE 1. A forklift truck steers with its rear wheels, not its front wheels like your car.
- FALSE 2. When you are planning to make a turn while traveling forward, you should steer your forklift to the opposite side of the road or isle...in the direction you are going to turn.
- TRUE 3. When traveling backward, the rear wheels should pass the corner and the front wheels should reach the corner before you start turning the steering wheel to make a turn.
- TRUE 4. A forklift truck operator must always watch the rear swing of the truck as well as the front swing of the load.
- FALSE 5. A forklift truck is much harder to steer when the forks are loaded.
- TRUE 6. A forklift truck operator should always travel with the forks four to six inches above the ground.
- TRUE 7. An operator should always inspect a load before he attempts to make a lift.
- TRUE 8. When picking up a load with a forklift truck, always approach the load squarely.
- TRUE 9. The forks should be spaced as widely as possible according to the load width and equally spaced from the sides of the carriage.
- FALSE 10. At times, it might become necessary to make a lift with only one fork.
- FALSE 11. At times, it might also become necessary to "pick up short", that is pick up a load with only part of your forks.
- TRUE 12. An operator should never put his head, hands or feet out of the truck cage.
- TRUE 13. Only the small Hyster forklift should ever be carried in the plant's elevators.
- FALSE 14. It is better to drive forward up a ramp when your truck is empty.
- TRUE 15. You should drive forward up a ramp and backwards down a ramp when your forks are loaded.

- Page 2 -
SECTION II QUIZ

- True 16. Always cross railroad tracks at a 45 degree angle.
- True 17. Passengers should never be carried on a forklift truck as it is designed for only one person...the operator.
- True 18. Before depositing a load, the operator should take the time to inspect the place where he is going to unload.
- True 19. You should never use full back tilt when high stacking. The safest condition is when the top of the mast is only a foot to 18 inches back from vertical.
- True 20. If you have to leave the fork truck unattended for even a short time, you should lower the forks and turn off the engine.

100

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION III QUIZ

North May

VINYL

1-24-80

- True 1. If the tractor is attached to the trailer, you should be sure to notify the driver that you are about to begin loading the trailer.
- FALSE 2. It is not necessary to chock the wheels of a trailer to be loaded if the tractor is attached.
- True 3. In addition to the dolly wheels, special jacks must be placed under the front of a trailer, when the tractor is not attached, before loading begins.
- True 4. Trailer floors should be checked for damage before loading begins.
- FALSE 5. The proper way to load a trailer is to load all of one side then all of the other side.
- True 6. If double stacking is required when loading a trailer, it should be done in the front and back so the extra weight will be on the axles.
- True 7. An employee should never be lifted with a forklift truck unless a caged worklift is used.
- True 8. When using a worklift, you must be sure that the safety pin is placed through the worklift mount and the forklift forks to prevent the worklift from sliding off the forks.
- FALSE 9. It is O.K. for an employee to ride to a work site if he is riding in a worklift.
- True 10. Unloading a trash dumpster should be done with forklift mast straight up, not tilted forward or backward.

ABERDEEN FORKLIFT TRAINING PROGRAM

90

SECTION II QUIZ

Alonzo McKiver

- T 1. A forklift truck steers with its rear wheels, not its front wheels like your car.
- T 2. When you are planning to make a turn while traveling forward, you should steer your forklift to the opposite side of the road or isle...in the direction you are going to turn.
- T 3. When traveling backward, the rear wheels should pass the corner and the front wheels should reach the corner before you start turning the steering wheel to make a turn.
- T 4. A forklift truck operator must always watch the rear swing of the truck as well as the front swing of the load.
- F 5. A forklift truck is much harder to steer when the forks are loaded.
- T 6. A forklift truck operator should always travel with the forks four to six inches above the ground.
- T 7. An operator should always inspect a load before he attempts to make a lift.
- T 8. When picking up a load with a forklift truck, always approach the load squarely.
- T 9. The forks should be spaced as widely as possible according to the load width and equally spaced from the sides of the carriage.
- F 10. At times, it might become necessary to make a lift with only one fork.
- F 11. At times, it might also become necessary to "pick up short", that is pick up a load with only part of your forks.
- T 12. An operator should never put his head, hands or feet out of the truck cage.
- F 13. Only the small Hyster forklift should ever be carried in the plant's elevators.
- F 14. It is better to drive forward up a ramp when your truck is empty.
- T 15. You should drive forward up a ramp and backwards down a ramp when your forks are loaded.

A

- Page 2 -
SECTION II QUIZ

- T 16. Always cross railroad tracks at a 45 degree angle.
- T 17. Passengers should never be carried on a forklift truck as it is designed for only one person...the operator.
- T 18. Before depositing a load, the operator should take the time to inspect the place where he is going to unload.
- T 19. You should never use full back tilt when high stacking. The safest condition is when the top of the mast is only a foot to 18 inches back from vertical.
- T 20. If you have to leave the fork truck unattended for even a short time, you should lower the forks and turn off the engine.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION III QUIZ

-
- T 1. If the tractor is attached to the trailer, you should be sure to notify the driver that you are about to begin loading the trailer.
- F 2. It is not necessary to chock the wheels of a trailer to be loaded if the tractor is attached.
- T 3. In addition to the dolly wheels, special jacks must be placed under the front of a trailer, when the tractor is not attached, before loading begins.
- T 4. Trailer floors should be checked for damage before loading begins.
- F 5. The proper way to load a trailer is to load all of one side then all of the other side.
- T 6. If double stacking is required when loading a trailer, it should be done in the front and back so the extra weight will be on the axles.
- F 7. An employee should never be lifted with a forklift truck unless a caged worklift is used.
- T 8. When using a worklift, you must be sure that the safety pin is placed through the worklift mount and the forklift forks to prevent the worklift from sliding off the forks.
- F 9. It is O.K. for an employee to ride to a work site if he is riding in a worklift.
- PT 10. Unloading a trash dumpster should be done with forklift mast straight up, not tilted forward or backward.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION I QUIZ

Daniel Darby Vinyl 1-24-80

- T 1. Good, competent, professional forklift operation is a safe operation and you can never be too experienced to learn more about safety.
- T 2. The first rule of safe forklift operation is to know the capacity of your truck.
- T 3. The load capacity of each of our forklift trucks is clearly marked on the identification plate on the truck.
- F 4. If you are in doubt about your forklift's ability to pick up a certain load, use the trial and error approach.
- T 5. A pre-work check of your forklift should be made to be sure it's working right and will operate safely.
- F 6. The further the center of the load is away from the front of the carriage, the larger the load you can pick up.
- F 7. All of the forklift trucks in the Aberdeen Plant are equipped with a hand brake.
- F 8. You should try to repair any problems you find during the pre-work check of the forklift truck.

100

A

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION II QUIZ

1-24-80

- Daniel Darby
- Vinyz
1. A forklift truck steers with its rear wheels, not its front wheels like your car.
2. When you are planning to make a turn while traveling forward, you should steer your forklift to the opposite side of the road or isle...in the direction you are going to turn.
3. When traveling backward, the rear wheels should pass the corner and the front wheels should reach the corner before you start turning the steering wheel to make a turn.
4. A forklift truck operator must always watch the rear swing of the truck as well as the front swing of the load.
5. A forklift truck is much harder to steer when the forks are loaded.
6. A forklift truck operator should always travel with the forks four to six inches above the ground.
7. An operator should always inspect a load before he attempts to make a lift.
8. When picking up a load with a forklift truck, always approach the load squarely.
9. The forks should be spaced as widely as possible according to the load width and equally spaced from the sides of the carriage.
10. At times, it might become necessary to make a lift with only one fork.
11. At times, it might also become necessary to "pick up short", that is pick up a load with only part of your forks.
12. An operator should never put his head, hands or feet out of the truck cage.
13. Only the small Hyster forklift should ever be carried in the plant's elevators.
14. It is better to drive forward up a ramp when your truck is empty.
15. You should drive forward up a ramp and backwards down a ramp when your forks are loaded.

- Page 2 -
SECTION II QUIZ

- T 16. Always cross railroad tracks at a 45 degree angle.
- T 17. Passengers should never be carried on a forklift truck as it is designed for only one person...the operator.
- T 18. Before depositing a load, the operator should take the time to inspect the place where he is going to unload.
- T 19. You should never use full back tilt when high stacking. The safest condition is when the top of the mast is only a foot to 18 inches back from vertical.
- T 20. If you have to leave the fork truck unattended for even a short time, you should lower the forks and turn off the engine.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION III QUIZ

Daniel Darby Vinyl 1-24-80

- T 1. If the tractor is attached to the trailer, you should be sure to notify the driver that you are about to begin loading the trailer.
- F 2. It is not necessary to chock the wheels of a trailer to be loaded if the tractor is attached.
- T 3. In addition to the dolly wheels, special jacks must be placed under the front of a trailer, when the tractor is not attached, before loading begins.
- T 4. Trailer floors should be checked for damage before loading begins.
- F 5. The proper way to load a trailer is to load all of one side then all of the other side.
- T 6. If double stacking is required when loading a trailer, it should be done in the front and back so the extra weight will be on the axles.
- T 7. An employee should never be lifted with a forklift truck unless a caged worklift is used.
- T 8. When using a worklift, you must be sure that the safety pin is placed through the worklift mount and the forklift forks to prevent the worklift from sliding off the forks.
- F 9. It is O.K. for an employee to ride to a work site if he is riding in a worklift.
- T 10. Unloading a trash dumpster should be done with forklift mast straight up, not tilted forward or backward.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION I QUIZ

-
- True 1. Good, competent, professional forklift operation is a safe operation and you can never be too experienced to learn more about safety.
- True 2. The first rule of safe forklift operation is to know the capacity of your truck.
- True 3. The load capacity of each of our forklift trucks is clearly marked on the identification plate on the truck.
- False 4. If you are in doubt about your forklift's ability to pick up a certain load, use the trial and error approach.
- True 5. A pre-work check of your forklift should be made to be sure it's working right and will operate safely.
- False 6. The further the center of the load is away from the front of the carriage, the larger the load you can pick up.
- False 7. All of the forklift trucks in the Aberdeen Plant are equipped with a hand brake.
- False 8. You should try to repair any problems you find during the pre-work check of the forklift truck.

(95)

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION II QUIZ

- TRUE 1. A forklift truck steers with its rear wheels, not its front wheels like your car.
- FALSE 2. When you are planning to make a turn while traveling forward, you should steer your forklift to the opposite side of the road or isle...in the direction you are going to turn.
- TRUE 3. When traveling backward, the rear wheels should pass the corner and the front wheels should reach the corner before you start turning the steering wheel to make a turn.
- TRUE 4. A forklift truck operator must always watch the rear swing of the truck as well as the front swing of the load.
- 5 TRUE 5. A forklift truck is much harder to steer when the forks are loaded.
- TRUE 6. A forklift truck operator should always travel with the forks four to six inches above the ground.
- TRUE 7. An operator should always inspect a load before he attempts to make a lift.
- TRUE 8. When picking up a load with a forklift truck, always approach the load squarely.
- TRUE 9. The forks should be spaced as widely as possible according to the load width and equally spaced from the sides of the carriage.
- FALSE 10. At times, it might become necessary to make a lift with only one fork.
- FALSE 11. At times, it might also become necessary to "pick up short", that is pick up a load with only part of your forks.
- TRUE 12. An operator should never put his head, hands or feet out of the truck cage.
- TRUE 13. Only the small Hyster forklift should ever be carried in the plant's elevators.
- FALSE 14. It is better to drive forward up a ramp when your truck is empty.
- TRUE 15. You should drive forward up a ramp and backwards down a ramp when your forks are loaded.

- Page 2 -
SECTION II QUIZ

- True 16. Always cross railroad tracks at a 45 degree angle.
- True 17. Passengers should never be carried on a forklift-truck as it is designed for only one person...the operator.
- True 18. Before depositing a load, the operator should take the time to inspect the place where he is going to unload.
- True 19. You should never use full back tilt when high stacking. The safest condition is when the top of the mast is only a foot to 18 inches back from vertical.
- True 20. If you have to leave the fork truck unattended for even a short time, you should lower the forks and turn off the engine.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION I QUIZ

Alonzo McKinnick

- T 1. Good, competent, professional forklift operation is a safe operation and you can never be too experienced to learn more about safety.
- T 2. The first rule of safe forklift operation is to know the capacity of your truck.
- T 3. The load capacity of each of our forklift trucks is clearly marked on the identification plate on the truck.
- T 4. If you are in doubt about your forklift's ability to pick up a certain load, use the trial and error approach.
- T 5. A pre-work check of your forklift should be made to be sure it's working right and will operate safely.
- F 6. The further the center of the load is away from the front of the carriage, the larger the load you can pick up.
- F 7. All of the forklift trucks in the Aberdeen Plant are equipped with a hand brake.
- F 8. You should try to repair any problems you find during the pre-work check of the forklift truck.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION III QUIZ

Verneta peter Viny Jan 24-80

- T 1. If the tractor is attached to the trailer, you should be sure to notify the driver that you are about to begin loading the trailer.
- F 2. It is not necessary to chock the wheels of a trailer to be loaded if the tractor is attached.
- T 3. In addition to the dolly wheels, special jacks must be placed under the front of a trailer, when the tractor is not attached, before loading begins.
- T 4. Trailer floors should be checked for damage before loading begins.
- F 5. The proper way to load a trailer is to load all of one side then all of the other side.
- T 6. If double stacking is required when loading a trailer, it should be done in the front and back so the extra weight will be on the axles.
- T 7. An employee should never be lifted with a forklift truck unless a caged worklift is used.
- T 8. When using a worklift, you must be sure that the safety pin is placed through the worklift mount and the forklift forks to prevent the worklift from sliding off the forks.
- F 9. It is O.K. for an employee to ride to a work site if he is riding in a worklift.
- T 10. Unloading a trash dumpster should be done with forklift mast straight up, not tilted forward or backward.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION I QUIZ

Doug Voore

1/3/80

- T 1. Good, competent, professional forklift operation is a safe operation and you can never be too experienced to learn more about safety.
- T 2. The first rule of safe forklift operation is to know the capacity of your truck.
- T 3. The load capacity of each of our forklift trucks is clearly marked on the identification plate on the truck.
- F 4. If you are in doubt about your forklift's ability to pick up a certain load, use the trial and error approach.
- T 5. A pre-work check of your forklift should be made to be sure it's working right and will operate safely.
- F 6. The further the center of the load is away from the front of the carriage, the larger the load you can pick up.
- F 7. All of the forklift trucks in the Aberdeen Plant are equipped with a hand brake.
- F 8. You should try to repair any problems you find during the pre-work check of the forklift truck.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION II QUIZ

Donna Vowse

1/3/80

- T 1. A forklift truck steers with its rear wheels, not its front wheels like your car.
- F 2. When you are planning to make a turn while traveling forward, you should steer your forklift to the opposite side of the road or isle...in the direction you are going to turn.
- T 3. When traveling backward, the rear wheels should pass the corner and the front wheels should reach the corner before you start turning the steering wheel to make a turn.
- T 4. A forklift truck operator must always watch the rear swing of the truck as well as the front swing of the load.
- F 5. A forklift truck is much harder to steer when the forks are loaded.
- T 6. A forklift truck operator should always travel with the forks four to six inches above the ground.
- T 7. An operator should always inspect a load before he attempts to make a lift.
- T 8. When picking up a load with a forklift truck, always approach the load squarely.
- T 9. The forks should be spaced as widely as possible according to the load width and equally spaced from the sides of the carriage.
- F 10. At times, it might become necessary to make a lift with only one fork.
- F 11. At times, it might also become necessary to "pick up short", that is pick up a load with only part of your forks.
- T 12. An operator should never put his head, hands or feet out of the truck.
- T 13. Only the small Hyster forklift should ever be carried in the plant's elevators.
- F 14. It is better to drive forward up a ramp when your truck is empty.
- T 15. You should drive forward up a ramp and backwards down a ramp when forks are loaded.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION III QUIZ

Doug Vogue

1/3/80

- T 1. If the tractor is attached to the trailer, you should be sure to notify the driver that you are about to begin loading the trailer.
- F 2. It is not necessary to chock the wheels of a trailer to be loaded if the tractor is attached.
- T 3. In addition to the dolly wheels, special jacks must be placed under the front of a trailer, when the tractor is not attached, before loading begins.
- T 4. Trailer floors should be checked for damage before loading begins.
- F 5. The proper way to load a trailer is to load all of one side then all of the other side.
- T 6. If double stacking is required when loading a trailer, it should be done in the front and back so the extra weight will be on the axles.
- T 7. An employee should never be lifted with a forklift truck unless a caged worklift is used.
- T 8. When using a worklift, you must be sure that the safety pin is placed through the worklift mount and the forklift forks to prevent the worklift from sliding off the forks.
- F 9. It is O.K. for an employee to ride to a work site if he is riding in a worklift.
- T 10. Unloading a trash dumpster should be done with forklift mast straight up, not tilted forward or backward.

95

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION II QUIZ

Verneta Peters

vinyl

Jan 24-80

- T
1. A forklift truck steers with its rear wheels, not its front wheels like your car.
- F
2. When you are planning to make a turn while traveling forward, you should steer your forklift to the opposite side of the road or isle...in the direction you are going to turn.
- T
3. When traveling backward, the rear wheels should pass the corner and the front wheels should reach the corner before you start turning the steering wheel to make a turn.
- T
4. A forklift truck operator must always watch the rear swing of the truck as well as the front swing of the load.
- F
5. A forklift truck is much harder to steer when the forks are loaded.
- T
6. A forklift truck operator should always travel with the forks four to six inches above the ground.
- T
7. An operator should always inspect a load before he attempts to make a lift.
- T
8. When picking up a load with a forklift truck, always approach the load squarely.
- T
9. The forks should be spaced as widely as possible according to the load width and equally spaced from the sides of the carriage.
- F
10. At times, it might become necessary to make a lift with only one fork.
- F
11. At times, it might also become necessary to "pick up short", that is, pick up a load with only part of your forks.
- T
12. An operator should never put his head, hands or feet out of the truck cage.
- T
13. Only the small Hyster forklift should ever be carried in the plant's elevators.
- F
14. It is better to drive forward up a ramp when your truck is empty.
- ~~T~~
15. You should drive forward up a ramp and backwards down a ramp when your forks are loaded.

- Page 2 -
SECTION II QUIZ

A

T 16. Always cross railroad tracks at a 45 degree angle.

T 17. Passengers should never be carried on a forklift truck as it is designed for only one person...the operator.

T 18. Before depositing a load, the operator should take the time to inspect the place where he is going to unload.

T 19. You should never use full back tilt when high stacking. The safest condition is when the top of the mast is only a foot to 18 inches back from vertical.

T 20. If you have to leave the fork truck unattended for even a short time, you should lower the forks and turn off the engine.

Steve Drouse
NAME

Vincil
DEPARTMENT

9/2/82
DATE

1. Excessive amounts of lead in the body can cause serious harm, including death.

True ☒

False ☐

2. The lead materials we have in this plant are powders used as heat stabilizers and color pigments in PVC compounds.

True ☒

False ☐

3. The exposure limit for lead is 50 micrograms of lead per cubic meter of air for any eight-hour work period.

4. The exposure limit for lead is lowered if you work more than eight (8) hours during a work period.

True ☐

False ☒

5. Lead used in this plant can enter the body by:

- A. Inhaling
- B. Swallowing
- C. Absorbing through the skin
- D. All of the above
- ☒ E. A & B Only

6. If you get lead material on your skin or clothing, you don't have to do anything about it because lead is not absorbed through your skin.

True ☐

False ☒

NOTE: If you think that was a "trick" question, you should think about your answer again.

7. Some lead tasks require breathing protection. Name one such task.

dust mask or oxygen mask

8. It is O.K. to take food, drinks, etc. into lead areas, provided you are careful to not let lead materials get into them.

True ☐

False ☒

9. Medical testing is used to make certain your lead exposure is not hurting you.

True ☒

False ☐

10. If the lead area ventilation systems are working and your medical tests and monitoring results are all "Good," you don't have to be concerned about lead exposures.

True ☐

False ☒

NOTE: If you're not sure about your answer, you need to think about it some more.

VAB.0001076944

NAME Charles Morris DEPARTMENT Verigil DATE 9/2/80

1. Excessive amounts of lead in the body can cause serious harm, including death.

True X False

2. The lead materials we have in this plant are powders used as heat stabilizers and color pigments in PVC compounds.

True X False

3. The exposure limit for lead is 50 micrograms of lead per cubic meter of air for any eight-hour work period.

4. The exposure limit for lead is lowered if you work more than eight (8) hours during a work period.

True X False

5. Lead used in this plant can enter the body by:

- A. Inhaling
- B. Swallowing
- C. Absorbing through the skin
- D. All of the above
- E. A & B Only

6. If you get lead material on your skin or clothing, you don't have to do anything about it because lead is not absorbed through your skin.

True False X

NOTE: If you think that was a "trick" question, you should think about your answer again.

7. Some lead tasks require breathing protection. Name one such task.

Charging a Blender or in the colorweigh room

8. It is O.K. to take food, drinks, etc. into lead areas, provided you are careful to not let lead materials get into them.

True False X

9. Medical testing is used to make certain your lead exposure is not hurting you.

True X False

10. If the lead area ventilation systems are working and your medical tests and monitoring results are all "Good," you don't have to be concerned about lead exposures.

True False X

NOTE: If you're not sure about your answer, you need to think about it some more.

NAME

Randy D. OHS

DEPARTMENT

VINYL

DATE

9-2-80

1. Excessive amounts of lead in the body can cause serious harm, including death.

True ☒False ☐

2. The lead materials we have in this plant are powders used as heat stabilizers and color pigments in PVC compounds.

True ☒False ☐

3. The exposure limit for lead is 50 micrograms of lead per cubic meter of air for any eight-hour work period.

4. The exposure limit for lead is lowered if you work more than eight (8) hours during a work period.

True ☒False ☐

5. Lead used in this plant can enter the body by:

- ☒ A. Inhaling
☒ B. Swallowing
C. Absorbing through the skin
D. All of the above
☒ E. A & B Only

6. If you get lead material on your skin or clothing, you don't have to do anything about it because lead is not absorbed through your skin.

True ☐False ☒

NOTE: If you think that was a "trick" question, you should think about your answer again.

7. Some lead tasks require breathing protection. Name one such task.

Emptying bags of lead

8. It is O.K. to take food, drinks, etc. into lead areas, provided you are careful to not let lead materials get into them.

True ☐False ☒

9. Medical testing is used to make certain your lead exposure is not hurting you.

True ☒False ☐

10. If the lead area ventilation systems are working and your medical tests and monitoring results are all "Good," you don't have to be concerned about lead exposures.

True ☐False ☒

NOTE: If you're not sure about your answer, you need to think about it some more.

VAB.0001076946

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION III QUIZ

Milton Hoskins

- T 1. If the tractor is attached to the trailer, you should be sure to notify the driver that you are about to begin loading the trailer.
- T 2. It is not necessary to chock the wheels of a trailer to be loaded if the tractor is attached.
- T 3. In addition to the dolly wheels, special jacks must be placed under the front of a trailer, when the tractor is not attached, before loading begins.
- T 4. Trailer floors should be checked for damage before loading begins.
- F 5. The proper way to load a trailer is to load all of one side then all of the other side.
- T 6. If double stacking is required when loading a trailer, it should be done in the front and back so the extra weight will be on the axles.
- T 7. An employee should never be lifted with a forklift truck unless a caged worklift is used.
- T 8. When using a worklift, you must be sure that the safety pin is placed through the worklift mount and the forklift forks to prevent the worklift from sliding off the forks.
- F 9. It is O.K. for an employee to ride to a work site if he is riding in a worklift.
- T 10. Unloading a trash dumpster should be done with forklift mast straight up, not tilted forward or backward.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION II QUIZ

- yes 1. A forklift truck steers with its rear wheels, not its front wheels like your car.
- yes 2. When you are planning to make a turn while traveling forward, you should steer your forklift to the opposite side of the road or isle...in the direction you are going to turn.
- no 3. When traveling backward, the rear wheels should pass the corner and the front wheels should reach the corner before you start turning the steering wheel to make a turn.
- yes 4. A forklift truck operator must always watch the rear swing of the truck as well as the front swing of the load.
- no 5. A forklift truck is much harder to steer when the forks are loaded.
- yes 6. A forklift truck operator should always travel with the forks four to six inches above the ground.
- yes 7. An operator should always inspect a load before he attempts to make a lift.
- yes 8. When picking up a load with a forklift truck, always approach the load squarely.
- no 9. The forks should be spaced as widely as possible according to the load width and equally spaced from the sides of the carriage.
- no 10. At times, it might become necessary to make a lift with only one fork.
- yes 11. At times, it might also become necessary to "pick up short", that is pick up a load with only part of your forks.
- yes 12. An operator should never put his head, hands or feet out of the truck cage.
- yes 13. Only the small Hyster forklift should ever be carried in the plant's elevators.
- no 14. It is better to drive forward up a ramp when your truck is empty.
- yes 15. You should drive forward up a ramp and backwards down a ramp when your forks are loaded.

- Page 2 -
SECTION II QUIZ

- Yes 16. Always cross railroad tracks at a 45 degree angle.
- Yes 17. Passengers should never be carried on a forklift truck as it is designed for only one person...the operator.
- Yes 18. Before depositing a load, the operator should take the time to inspect the place where he is going to unload.
- No 19. You should never use full back tilt when high stacking. The safest condition is when the top of the mast is only a foot to 18 inches back from vertical.
- Yes 20. If you have to leave the fork truck unattended for even a short time, you should lower the forks and turn off the engine.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION II QUIZ

Milton Hawkins

- T 1. A forklift truck steers with its rear wheels, not its front wheels like your car.
- T 2. When you are planning to make a turn while traveling forward, you should steer your forklift to the opposite side of the road or isle...in the direction you are going to turn.
- T 3. When traveling backward, the rear wheels should pass the corner and the front wheels should reach the corner before you start turning the steering wheel to make a turn.
- F 4. A forklift truck operator must always watch the rear swing of the truck as well as the front swing of the load.
- F 5. A forklift truck is much harder to steer when the forks are loaded.
- T 6. A forklift truck operator should always travel with the forks four to six inches above the ground.
- T 7. An operator should always inspect a load before he attempts to make a lift.
- T 8. When picking up a load with a forklift truck, always approach the load squarely.
- T 9. The forks should be spaced as widely as possible according to the load width and equally spaced from the sides of the carriage.
- F 10. At times, it might become necessary to make a lift with only one fork.
- F 11. At times, it might also become necessary to "pick up short", that is pick up a load with only part of your forks.
- T 12. An operator should never put his head, hands or feet out of the truck cage.
- T 13. Only the small Hyster forklift should ever be carried in the plant's elevators.
- F 14. It is better to drive forward up a ramp when your truck is empty.
- T 15. You should drive forward up a ramp and backwards down a ramp when your forks are loaded.

A

- Page 2 -
SECTION II QUIZ

- T 16. Always cross railroad tracks at a 45 degree angle.
- T 17. Passengers should never be carried on a forklift truck as it is designed for only one person...the operator.
- T 18. Before depositing a load, the operator should take the time to inspect the place where he is going to unload.
- T 19. You should never use full back tilt when high stacking. The safest condition is when the top of the mast is only a foot to 18 inches back from vertical.
- T 20. If you have to leave the fork truck unattended for even a short time, you should lower the forks and turn off the engine.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION I QUIZ

Charles Smith

- Yes 1. Good, competent, professional forklift operation is a safe operation and you can never be too experienced to learn more about safety.
- Yes 2. The first rule of safe forklift operation is to know the capacity of your truck.
- Yes 3. The load capacity of each of our forklift trucks is clearly marked on the identification plate on the truck.
- No 4. If you are in doubt about your forklift's ability to pick up a certain load, use the trial and error approach.
- Yes 5. A pre-work check of your forklift should be made to be sure it's working right and will operate safely.
- No 6. The further the center of the load is away from the front of the carriage, the larger the load you can pick up.
- No 7. All of the forklift trucks in the Aberdeen Plant are equipped with a hand brake.
- Yes 8. You should try to repair any problems you find during the pre-work check of the forklift truck.

ABERDEEN FORKLIFT TRAINING PROGRAM

SECTION I QUIZ

Milton Hobkins

- True 1. Good, competent, professional forklift operation is a safe operation and you can never be too experienced to learn more about safety.
- True 2. The first rule of safe forklift operation is to know the capacity of your truck.
- True 3. The load capacity of each of our forklift trucks is clearly marked on the identification plate on the truck.
- False 4. If you are in doubt about your forklift's ability to pick up a certain load, use the trial and error approach.
- True 5. A pre-work check of your forklift should be made to be sure it's working right and will operate safely.
- False 6. The further the center of the load is away from the front of the carriage, the larger the load you can pick up.
- True 7. All of the forklift trucks in the Aberdeen Plant are equipped with a hand brake.
- False 8. You should try to repair any problems you find during the pre-work check of the forklift truck.

-TEST, 1982-

NAME John Dixon Jr DEPARTMENT Drafting DATE MAY 29, 1980

1. Excessive amounts of lead in the body can cause serious harm, including death.

True ☒ False ☐

LEAD EXPOSURE TRAINING

-TEST, 1979-

NAME Alonzomckinzie DEPARTMENT Vingy 1 DATE 1-24-80

1. Excessive amounts of lead in the body can cause serious harm, including death.

True ☒ False ☐

2. The lead materials we have in this plant are powders used as heat stabilizers and color pigments in PVC compounds.

True ☒ False ☐

3. The exposure limit for lead is 50 micrograms of lead per cubic meter of air for any eight-hour work period.

4. The exposure limit for lead is lowered if you work more than eight (8) hours during a work period.

True ☒ False ☐

5. Lead used in this plant can enter the body by:

- A. Inhaling
B. Swallowing
C. Absorbing through the skin
D. All of the above
☒ E. A & B Only

6. If you get lead material on your skin or clothing, you don't have to do anything about it because lead is not absorbed through your skin.

True ☐ False ☒

NOTE: If you think that was a "trick" question, you should think about your answer again.

7. Some lead tasks require breathing protection. Name one such task.

Filling in Coloring Pigment Room 1 and 2

8. It is O.K. to take food, drinks, etc. into lead areas, provided you are careful to not let lead materials get into them.

True ☐ False ☒

9. Medical testing is used to make certain your lead exposure is not hurting you.

True ☒ False ☐

10. If the lead area ventilation systems are working and your medical tests and monitoring results are all "Good," you don't have to be concerned about lead exposures.

True ☐ False ☒

NOTE: If you're not sure about your answer, you need to think about it some more.

VAB.0001076954

-TEST, 1987-

AL BARFIELD

NAME

PROCESS ENGINEERING

DEPARTMENT

5/29/80

DATE

1. Excessive amounts of lead in the body can cause serious harm, including death.

True ☒False ☐

2. The lead materials we have in this plant are powders used as heat stabilizers and color pigments in PVC compounds.

True ☒False ☐

3. The exposure limit for lead is 50 micrograms of lead per cubic meter of air for any eight-hour work period.

4. The exposure limit for lead is lowered if you work more than eight (8) hours during a work period.

True ☒False ☐

5. Lead used in this plant can enter the body by:

- A. Inhaling
B. Swallowing
C. Absorbing through the skin
D. All of the above
E. A & B Only

6. If you get lead material on your skin or clothing, you don't have to do anything about it because lead is not absorbed through your skin.

True ☐False ☒

NOTE: If you think that was a "trick" question, you should think about your answer again.

7. Some lead tasks require breathing protection. Name one such task.

Transporting the lead compounds

8. It is O.K. to take food, drinks, etc. into lead areas, provided you are careful to not let lead materials get into them.

True ☐False ☒

9. Medical testing is used to make certain your lead exposure is not hurting you.

True ☒False ☐

10. If the lead area ventilation systems are working and your medical tests and monitoring results are all "Good," you don't have to be concerned about lead exposures.

True ☐False ☒

NOTE: If you're not sure about your answer, you need to think about it some more.

VAB.0001076955

ADARON Dobson
NAME

Vinyl
DEPARTMENT

1-18-80
DATE

- ✓ 1. Excessive amounts of lead in the body can cause serious harm, including death.

True ☒ False ☐

- ✓ 2. The lead materials we have in this plant are powders used as heat stabilizers and color pigments in PVC compounds.

True ☒ False ☐

- X 3. The exposure limit for lead is 33 micrograms of lead per cubic meter of air for any eight-hour work period.

- ✓ 4. The exposure limit for lead is lowered if you work more than eight (8) hours during a work period.

True ☒ False ☐

- ✓ 5. Lead used in this plant can enter the body by:

- ☒ A. Inhaling
☒ B. Swallowing
C. Absorbing through the skin
D. All of the above
☒ E. A & B Only

- ✓ 6. If you get lead material on your skin or clothing, you don't have to do anything about it because lead is not absorbed through your skin.

True ☐ False ☒

NOTE: If you think that was a "trick" question, you should think about your answer again.

- ✓ 7. Some lead tasks require breathing protection. Name one such task.

Mixing Station

- ✓ 8. It is O.K. to take food, drinks, etc. into lead areas, provided you are careful to not let lead materials get into them.

True ☐ False ☒

- ✓ 9. Medical testing is used to make certain your lead exposure is not hurting you.

True ☒ False ☐

- ✓ 10. If the lead area ventilation systems are working and your medical tests and monitoring results are all "Good," you don't have to be concerned about lead exposures.

True ☐ False ☒

NOTE: If you're not sure about your answer, you need to think about it some more.

-TEST, 1979-

80

NAME LARRY HUBBARD

DEPARTMENT Vinyl

DATE Jan. 18, 1980

1. Excessive amounts of lead in the body can cause serious harm, including death.

True ☒

False ☐

2. The lead materials we have in this plant are powders used as heat stabilizers and color pigments in PVC compounds.

True ☒

False ☐

3. The exposure limit for lead is 32 micrograms of lead per cubic meter of air for any eight-hour work period.

4. The exposure limit for lead is lowered if you work more than eight (8) hours during a work period.

True ☒

False ☐

5. Lead used in this plant can enter the body by:

- A. Inhaling
- B. Swallowing
- C. Absorbing through the skin
- D. All of the above
- ☒ E. A & B Only

6. If you get lead material on your skin or clothing, you don't have to do anything about it because lead is not absorbed through your skin.

True ☐

False ☒

NOTE: If you think that was a "trick" question, you should think about your answer again.

7. Some lead tasks require breathing protection. Name one such task.

A FACE MASK

8. It is O.K. to take food, drinks, etc. into lead areas, provided you are careful to not let lead materials get into them.

True ☐

False ☒

9. Medical testing is used to make certain your lead exposure is not hurting you.

True ☒

False ☐

10. If the lead area ventilation systems are working and your medical tests and monitoring results are all "Good," you don't have to be concerned about lead exposures.

True ☐

False ☒

NOTE: If you're not sure about your answer, you need to think about it some more.

VAB.0001076957

NAME Michael D. Clayton

DEPARTMENT V. N. V.

DATE 1-8-80

1. Excessive amounts of lead in the body can cause serious harm, including death.

True ☒

False ☐

2. The lead materials we have in this plant are powders used as heat stabilizers and color pigments in PVC compounds.

True ☒

False ☐

3. The exposure limit for lead is 50 micrograms of lead per cubic meter of air for any eight-hour work period.

4. The exposure limit for lead is lowered if you work more than eight (8) hours during a work period.

True ☒

False ☐

5. Lead used in this plant can enter the body by:

- A. Inhaling
- B. Swallowing
- C. Absorbing through the skin
- D. All of the above
- ☒ E. A & B Only

6. If you get lead material on your skin or clothing, you don't have to do anything about it because lead is not absorbed through your skin.

True ☐

False ☒

NOTE: If you think that was a "trick" question, you should think about your answer again.

7. Some lead tasks require breathing protection. Name one such task.

Weighting lead

8. It is O.K. to take food, drinks, etc. into lead areas, provided you are careful to not let lead materials get into them.

True ☐

False ☒

9. Medical testing is used to make certain your lead exposure is not hurting you.

True ☒

False ☐

10. If the lead area ventilation systems are working and your medical tests and monitoring results are all "Good," you don't have to be concerned about lead exposures.

True ☐

False ☒

NOTE: If you're not sure about your answer, you need to think about it some more.

100

-TEST, 1979-

Bill Caldwell

Vingl

1/18/80

NAME

DEPARTMENT

DATE

1. Excessive amounts of lead in the body can cause serious harm, including death.

True

☒

False

☐

2. The lead materials we have in this plant are powders used as heat stabilizers and color pigments in PVC compounds.

True

☒

False

☐

3. The exposure limit for lead is 50 micrograms of lead per cubic meter of air for any eight-hour work period.

4. The exposure limit for lead is lowered if you work more than eight (8) hours during a work period.

True

☒

False

☐

5. Lead used in this plant can enter the body by:

- A. Inhaling
- B. Swallowing
- C. Absorbing through the skin
- D. All of the above
- ☒ E. A & B Only

6. If you get lead material on your skin or clothing, you don't have to do anything about it because lead is not absorbed through your skin.

True

☐

False

☒

NOTE: If you think that was a "trick" question, you should think about your answer again.

7. Some lead tasks require breathing protection. Name one such task.

LOADING LEAD INTO PROCESSING LINES - WEIGHING LEAD SAMPLES

8. It is O.K. to take food, drinks, etc. into lead areas, provided you are careful to not let lead materials get into them.

True

☐

False

☒

9. Medical testing is used to make certain your lead exposure is not hurting you.

True

☒

False

☐

10. If the lead area ventilation systems are working and your medical tests and monitoring results are all "Good," you don't have to be concerned about lead exposures.

True

☐

False

☒

NOTE: If you're not sure about your answer, you need to think about it some more.

VAB.0001076959

Daniel Darby
NAME

Ving
DEPARTMENT

7-24-80
DATE

1. Excessive amounts of lead in the body can cause serious harm, including death.

True ☒

False ☐

2. The lead materials we have in this plant are powders used as heat stabilizers and color pigments in PVC compounds.

True ☒

False ☐

3. The exposure limit for lead is 50 micrograms of lead per cubic meter of air for any eight-hour work period.

4. The exposure limit for lead is lowered if you work more than eight (8) hours during a work period.

True ☒

False ☐

5. Lead used in this plant can enter the body by:

- A. Inhaling
- B. Swallowing
- C. Absorbing through the skin
- D. All of the above
- ☒ E. A & B Only

6. If you get lead material on your skin or clothing, you don't have to do anything about it because lead is not absorbed through your skin.

True ☐

False ☒

NOTE: If you think that was a "trick" question, you should think about your answer again.

7. Some lead tasks require breathing protection. Name one such task.

Blending

8. It is O.K. to take food, drihks, etc. into lead areas, provided you are careful to not let lead materials get into them.

True ☐

False ☒

9. Medical testing is used to make certain your lead exposure is not hurting you.

True ☒

False ☐

10. If the lead area ventilation systems are working and your medical tests and monitoring results are all "Good," you don't have to be concerned about lead exposures.

True ☐

False ☒

NOTE: If you're not sure about your answer, you need to think about it some more.

95

VCM EXPOSURE TRAINING

-TEST, 1979-

Alonzo McKinnick
NAME

Viny
DEPARTMENT

1-25-80
DATE

1. Evidence has been found that exposure to high-level concentrations of VCM over long periods of time could cause cancer of the liver.
True(☒) False()
2. A finger bone disease, acraosteolysis ("AOL"), has been linked to the manual cleaning of PVC reactors.
True(☒) False()
3. Liquid VCM can cause severe frostbite.
True(☒) False()
- 5 4. The exposure limits for VCM are 1.0 ppm average for any eight hour period and 1.000 ppm for any 15 minute period.
5. The three VCM regulated areas in the plant are:
 - A. Dry blend basement, Q.C. Lab and the Plasticizer Tank Farm.
 - B. Plasticizer Building, Boiler House and the East Warehouse.
 - ☒ C. VCM Tank Farm and the two large reactor areas.
6. If you have no business in a VCM regulated area, you must stay out.
True(☒) False()
7. Respiratory equipment (gas mask, air-line respirators, Scott Air-Pack, etc.) is required above (but not below):
☒ (A) 1.0 ppm (B) 0.5 ppm (C) 10.0 ppm
8. Our Honeywell continuous monitors alarm when 1.0 ppm is detected in an area.
9. We monitor your VCM exposure to:
 - A. Minimize your exposure to VCM.
 - B. Monitor progress in reducing VCM concentrations.
 - ☒ C. Both A & B.
 - D. To make sure we have a record.
10. Protective clothing is required for certain jobs.
True(☒) False()

10

A

VCM EXPOSURE TRAINING

-TEST, 1979-

Doug Vogue
NAME

VINYL
DEPARTMENT

1/3/80
DATE

1. Evidence has been found that exposure to high-level concentrations of VCM over long periods of time could cause cancer of the liver.
True(☒) False()
2. A finger bone disease, acraosteolysis ("AOL"), has been linked to the manual cleaning of PVC reactors.
True(☒) False()
3. Liquid VCM can cause severe frostbite.
True(☒) False()
4. The exposure limits for VCM are 1.0 ppm average for any eight hour period and 5.0 ppm for any 15 minute period.
5. The three VCM regulated areas in the plant are:
A. Dry blend basement, Q.C. Lab and the Plasticizer Tank Farm.
B. Plasticizer Building, Boiler House and the East Warehouse.
☒ C. VCM Tank Farm and the two large reactor areas.
6. If you have no business in a VCM regulated area, you must stay out.
True(☒) False()
7. Respiratory equipment (gas mask, air-line respirators, Scott Air-Pack, etc.) is required above (but not below):
☒ (A) 1.0 ppm (B) 0.5 ppm (C) 10.0 ppm
8. Our Honeywell continuous monitors alarm when ~~1.0~~ 5.0 ppm is detected in an area.
9. We monitor your VCM exposure to:
A. Minimize your exposure to VCM.
B. Monitor progress in reducing VCM concentrations.
☒ C. Both A & B.
D. To make sure we have a record.
10. Protective clothing is required for certain jobs.
True(☒) False()

VCM EXPOSURE TRAINING

-TEST, 1980-

ROBERT RICKERT
NAME

DEPARTMENT

6-380
DATE

1. Evidence has been found that exposure to high-level concentrations of VCM over long periods of time could cause cancer of the liver.
True(✓) False()
2. A finger bone disease, acraosteolysis ("AOL"), has been linked to the manual cleaning of PVC reactors.
True(✓) False()
3. Liquid VCM can cause severe frostbite.
True(✓) False()
4. The exposure limits for VCM are 1 ppm average for any eight hour period and 5 ppm for any 15 minute period.
5. The three VCM regulated areas in the plant are:
 - A. Dry blend basement, Q.C. Lab and the Plasticizer Tank Farm.
 - B. Plasticizer Building, Boiler House and the East Warehouse.
 - ③ C. VCM Tank Farm and the two large reactor areas.
6. If you have no business in a VCM regulated area, you must stay out.
True(✓) False()
7. Respiratory equipment (gas mask, air-line respirators, Scott Air-Pack, etc.) is required above (but not below):
(A) 1.0 ppm (B) 0.5 ppm (C) 10.0 ppm
8. Our Honeywell continuous monitors alarm when 1 ppm is detected in an area.
9. We monitor your VCM exposure to:
 - A. Minimize your exposure to VCM.
 - B. Monitor progress in reducing VCM concentrations.
 - ③ C. Both A & B.
 - D. To make sure we have a record.
10. Protective clothing is required for certain jobs.
True(✓) False()

VCM EXPOSURE TRAINING

-TEST, 1980-

NAME Charles Woods

DEPARTMENT VINYL

DATE 9-2-80

1. Evidence has been found that exposure to high-level concentrations of VCM over long periods of time could cause cancer of the liver.
True(☒) False()
2. A finger bone disease, acraosteolysis ("AOL"), has been linked to the manual cleaning of PVC reactors.
True(☒) False()
3. Liquid VCM can cause severe frostbite.
True(☒) False()
4. The exposure limits for VCM are 1 ppm average for any eight hour period and 10 ppm for any 15 minute period.
5. The three VCM regulated areas in the plant are:
 - A. Dry blend basement, Q.C. Lab and the Plasticizer Tank Farm.
 - B. Plasticizer Building, Boiler House and the East Warehouse.
 - ☒ C. VCM Tank Farm and the two large reactor areas.
6. If you have no business in a VCM regulated area, you must stay out.
True(☒) False()
7. Respiratory equipment (gas mask, air-line respirators, Scott Air-Pack, etc.) is required above (but not below):
☒ (A) 1.0 ppm (B) 0.5 ppm (C) 10.0 ppm
8. Our Honeywell continuous monitors alarm when above 1.0 ppm is detected in an area.
9. We monitor your VCM exposure to:
 - A. Minimize your exposure to VCM.
 - B. Monitor progress in reducing VCM concentrations.
 - ☒ C. Both A & B.
 - D. To make sure we have a record.
10. Protective clothing is required for certain jobs.
True(☒) False()

VCM EXPOSURE TRAINING

-TEST, 1980-

Steve Dwyer
NAME

Plant
DEPARTMENT

9/2/80
DATE

1. Evidence has been found that exposure to high-level concentrations of VCM over long periods of time could cause cancer of the liver.
True(☒) False()
2. A finger bone disease, acraosteolysis ("AOL"), has been linked to the manual cleaning of PVC reactors.
True(☒) False()
3. Liquid VCM can cause severe frostbite.
True(☒) False()
4. The exposure limits for VCM are ppm average for any eight hour period and 10 ppm for any 15 minute period.
5. The three VCM regulated areas in the plant are:
 - A. Dry blend basement, Q.C. Lab and the Plasticizer Tank Farm.
 - B. Plasticizer Building, Boiler House and the East Warehouse.
 - C. VCM Tank Farm and the two large reactor areas.
6. If you have no business in a VCM regulated area, you must stay out.
True(☒) False()
7. Respiratory equipment (gas mask, air-line respirators, Scott Air-Pack, etc.) is required above (but not below):
(A) 1.0 ppm (B) 0.5 ppm (C) 10.0 ppm
8. Our Honeywell continuous monitors alarm when 4,000 ppm is detected in an area.
9. We monitor your VCM exposure to:
 - A Minimize your exposure to VCM.
 - B. Monitor progress in reducing VCM concentrations.
 - C. Both A & B.
 - D. To make sure we have a record.
10. Protective clothing is required for certain jobs.
True(☒) False()

VCM EXPOSURE TRAINING

-TEST, 1980-

NAME Randy D. Otts DEPARTMENT VINYL DATE 9-2-80

1. Evidence has been found that exposure to high-level concentrations of VCM over long periods of time could cause cancer of the liver.
True(☒) False(☐)
2. A finger bone disease, acraosteolysis ("AOL"), has been linked to the manual cleaning of PVC reactors.
True(☒) False(☐)
3. Liquid VCM can cause severe frostbite.
True(☒) False(☐)
4. The exposure limits for VCM are 1 ppm ppm average for any eight hour period and 5 ppm for any 15 minute period.
5. The three VCM regulated areas in the plant are:
 - A. Dry blend basement, Q.C. Lab and the Plasticizer Tank Farm.
 - B. Plasticizer Building, Boiler House and the East Warehouse.
 - ☒ C. VCM Tank Farm and the two large reactor areas.
6. If you have no business in a VCM regulated area, you must stay out.
True(☒) False(☐)
7. Respiratory equipment (gas mask, air-line respirators, Scott Air-Pack, etc.) is required above (but not below):
(A) 1.0 ppm (B) 0.5 ppm (C) 10.0 ppm
8. Our Honeywell continuous monitors alarm when 1.1 ppm is detected in an area.
9. We monitor your VCM exposure to:
 - A. Minimize your exposure to VCM.
 - B. Monitor progress in reducing VCM concentrations.
 - ☒ C. Both A & B.
 - D. To make sure we have a record.
10. Protective clothing is required for certain jobs.
True(☒) False(☐)

VCM EXPOSURE TRAINING

-TEST, 1980-

John DIXON Jr
NAME

Drafting
DEPARTMENT

May 29, 1980
DATE

1. Evidence has been found that exposure to high-level concentrations of VCM over long periods of time could cause cancer of the liver.
True(✓) False()
2. A finger bone disease, acraosteolysis ("AOL"), has been linked to the manual cleaning of PVC reactors.
True(✓) False()
3. Liquid VCM can cause severe frostbite.
True(✓) False()
4. The exposure limits for VCM are 1 ppm average for any eight hour period and 5 ppm for any 15 minute period.
5. The three VCM regulated areas in the plant are:
A. Dry blend basement, Q.C. Lab and the Plasticizer Tank Farm.
B. Plasticizer Building, Boiler House and the East Warehouse.
C. VCM Tank Farm and the two large reactor areas.
6. If you have no business in a VCM regulated area, you must stay out.
True(✓) False()
7. Respiratory equipment (gas mask, air-line respirators, Scott Air-Pack, etc.) is required above (but not below):
(A) 1.0 ppm (B) 0.5 ppm (C) 10.0 ppm
8. Our Honeywell continuous monitors alarm when 1 ppm is detected in an area.
9. We monitor your VCM exposure to:
A. Minimize your exposure to VCM.
B. Monitor progress in reducing VCM concentrations.
C. Both A & B.
D. To make sure we have a record.
10. Protective clothing is required for certain jobs.
True(✓) False()

VCM EXPOSURE TRAINING

-TEST, 1980-

NAME ALICE JAMES

DEPARTMENT Process Engineering

DATE Aug 13, 1980

1. Evidence has been found that exposure to high-level concentrations of VCM over long periods of time could cause cancer of the liver.
True (☒) False ()
2. A finger bone disease, acraosteolysis ("AOL"), has been linked to the manual cleaning of PVC reactors.
True (☒) False ()
3. Liquid VCM can cause severe frostbite.
True (☒) False ()
4. The exposure limits for VCM are 1 ppm average for any eight hour period and 5 ppm for any 15 minute period.
5. The three VCM regulated areas in the plant are:
 - A. Dry blend basement, Q.C. Lab and the Plasticizer Tank Farm.
 - B. Plasticizer Building, Boiler House and the East Warehouse.
 - ☒ C. VCM Tank Farm and the two large reactor areas.
6. If you have no business in a VCM regulated area, you must stay out.
True (☒) False ()
7. Respiratory equipment (gas mask, air-line respirators, Scott Air-Pack, etc.) is required above (but not below):
(A) 1.0 ppm (B) ☒ 0.5 ppm (C) 10.0 ppm
8. Our Honeywell continuous monitors alarm when 1 ppm is detected in an area.
9. We monitor your VCM exposure to:
 - A. Minimize your exposure to VCM.
 - B. Monitor progress in reducing VCM concentrations.
 - ☒ C. Both A & B.
 - D. To make sure we have a record.
10. Protective clothing is required for certain jobs.
True (☒) False ()

VCM EXPOSURE TRAINING

-TEST, 1980-

NAME _____

DEPARTMENT _____

DATE _____

1. Evidence has been found that exposure to high-level concentrations of VCM over long periods of time could cause cancer of the liver.
True(☒) False(☐)
2. A finger bone disease, acraosteolysis ("AOL"), has been linked to the manual cleaning of PVC reactors.
True(☒) False(☐)
3. Liquid VCM can cause severe frostbite.
True(☒) False(☐)
4. The exposure limits for VCM are 1 ppm average for any eight hour period and 5 ppm for any 15 minute period.
5. The three VCM regulated areas in the plant are:
 - A. Dry blend basement, Q.C. Lab and the Plasticizer Tank Farm.
 - B. Plasticizer Building, Boiler House and the East Warehouse.
 - ☒ C. VCM Tank Farm and the two large reactor areas.
6. If you have no business in a VCM regulated area, you must stay out.
True(☒) False(☐)
7. Respiratory equipment (gas mask, air-line respirators, Scott Air-Pack, etc.) is required above (but not below):
☒ (A) 1.0 ppm (B) 0.5 ppm (C) 10.0 ppm
8. Our Honeywell continuous monitors alarm when 1.0 ppm is detected in an area.
9. We monitor your VCM exposure to:
 - A. Minimize your exposure to VCM.
 - B. Monitor progress in reducing VCM concentrations.
 - ☒ C. Both A & B.
 - D. To make sure we have a record.
10. Protective clothing is required for certain jobs.
True(☒) False(☐)

VCM EXPOSURE TRAINING

-TEST, 1980-

AL BARFIELD
NAME

PROCESS ENGINEERING
DEPARTMENT

5/29/80
DATE

1. Evidence has been found that exposure to high-level concentrations of VCM over long periods of time could cause cancer of the liver.
True(✓) False()
2. A finger bone disease, acraosteolysis ("AOL"), has been linked to the manual cleaning of PVC reactors.
True(✓) False()
3. Liquid VCM can cause severe frostbite.
True(✓) False()
4. The exposure limits for VCM are 1 ppm average for any eight hour period and 5 ppm for any 15 minute period.
5. The three VCM regulated areas in the plant are:
A. Dry blend basement, Q.C. Lab and the Plasticizer Tank Farm.
B. Plasticizer Building, Boiler House and the East Warehouse.
C. VCM Tank Farm and the two large reactor areas.
6. If you have no business in a VCM regulated area, you must stay out.
True(✓) False()
7. Respiratory equipment (gas mask, air-line respirators, Scott Air-Pack, etc.) is required above (but not below):
(A) 1.0 ppm (B) 0.5 ppm (C) 10.0 ppm
8. Our Honeywell continuous monitors alarm when _____ ppm is detected in an area.
9. We monitor your VCM exposure to:
A. Minimize your exposure to VCM.
B. Monitor progress in reducing VCM concentrations.
C. Both A & B.
D. To make sure we have a record.
10. Protective clothing is required for certain jobs.
True(✓) False()

VCM EXPOSURE TRAINING

-TEST, 1980

75
A
NAME Arvon Dobson

DEPARTMENT Vinyl

DATE 1-18-80

- ✓ 1. Evidence has been found that exposure to high-level concentrations of VCM over long periods of time could cause cancer of the liver.
True(✓) False()
- ✗ 2. A finger bone disease, acraosteolysis ("AOL"), has been linked to the manual cleaning of PVC reactors.
True() False(✓)
- ✓ 3. Liquid VCM can cause severe frostbite.
True(✓) False()
- ✗ 4. The exposure limits for VCM are 1.0 ppm average for any eight hour period and 1.0 ppm for any 15 minute period.
- ✓ 5. The three VCM regulated areas in the plant are:
 - Ⓐ Dry blend basement, Q.C. Lab and the Plasticizer Tank Farm.
 - B. Plasticizer Building, Boiler House and the East Warehouse.
 - C. VCM Tank Farm and the two large reactor areas.
- ✗ 6. If you have no business in a VCM regulated area, you must stay out.
True() False(✓)
- ✓ 7. Respiratory equipment (gas mask, air-line respirators, Scott Air-Pack, etc.) is required above (but not below):
 - (A) 1.0 ppm
 - (B) 0.5 ppm
 - (C) 10.0 ppm
- ✓ 8. Our Honeywell continuous monitors alarm when 5.0 ppm is detected in an area.
- ✓ 9. We monitor your VCM exposure to:
 - Ⓐ Minimize your exposure to VCM.
 - Ⓑ Monitor progress in reducing VCM concentrations.
 - C. Both A & B.
 - D. To make sure we have a record.
- ✓ 10. Protective clothing is required for certain jobs.
True(✓) False()

VCM EXPOSURE TRAINING

-TEST 1980

80

HARRY HUBBARD
NAME

Vinyl
DEPARTMENT

JAN. 18, 1980
DATE

1. Evidence has been found that exposure to high-level concentrations of VCM over long periods of time could cause cancer of the liver.

True(✓) False()

2. A finger bone disease, acraosteolysis ("AOL"), has been linked to the manual cleaning of PVC reactors.

True() False(✓)

3. Liquid VCM can cause severe frostbite.

True(✓) False()

4. The exposure limits for VCM are 1-1,000 ppm average for any eight hour period and 1,000-+ ppm for any 15 minute period.

5. The three VCM regulated areas in the plant are:

- A. Dry blend basement, Q.C. Lab and the Plasticizer Tank Farm.
B. Plasticizer Building, Boiler House and the East Warehouse.
C. VCM Tank Farm and the two large reactor areas.

6. If you have no business in a VCM regulated area, you must stay out.

True(✓) False()

7. Respiratory equipment (gas mask, air-line respirators, Scott Air-Pack, etc.) is required above (but not below):

(A) 1.0 ppm (B) 0.5 ppm (C) 10.0 ppm

8. Our Honeywell continuous monitors alarm when 5 ppm is detected in an area.

9. We monitor your VCM exposure to:

- A. Minimize your exposure to VCM.
B. Monitor progress in reducing VCM concentrations.
C. Both A & B.
D. To make sure we have a record.

10. Protective clothing is required for certain jobs.

True(✓) False()

VCM EXPOSURE TRAINING

-TEST 1980

95

NAME Michael D. Cloutier

DEPARTMENT V. NYL

DATE 1-18-80

1. Evidence has been found that exposure to high-level concentrations of VCM over long periods of time could cause cancer of the liver.
True(☒) False()
2. A finger bone disease, acraosteolysis ("AOL"), has been linked to the manual cleaning of PVC reactors.
True(☒) False()
3. Liquid VCM can cause severe frostbite.
True(☒) False()
4. The exposure limits for VCM are 1 ppm average for any eight hour period and 3 (5) ppm for any 15 minute period.
5. The three VCM regulated areas in the plant are:
 - A. Dry blend basement, Q.C. Lab and the Plasticizer Tank Farm.
 - B. Plasticizer Building, Boiler House and the East Warehouse.
 - ☒ C. VCM Tank Farm and the two large reactor areas.
6. If you have no business in a VCM regulated area, you must stay out.
True(☒) False()
7. Respiratory equipment (gas mask, air-line respirators, Scott Air-Pack, etc.) is required above (but not below):
☒ (A) 1.0 ppm (B) 0.5 ppm (C) 10.0 ppm
8. Our Honeywell continuous monitors alarm when over 15 ppm is detected in an area.
9. We monitor your VCM exposure to:
 - A. Minimize your exposure to VCM.
 - B. Monitor progress in reducing VCM concentrations.
 - ☒ C. Both A & B.
 - D. To make sure we have a record.
10. Protective clothing is required for certain jobs.
True(☒) False()