O'BRIEN

REGISTERED
REG'N. No. 75131
DATE 5-13-6

"SEVENTY-FIVE"®
Gloss
HOUSE PAINT

SUNRAY

ONE GALLON

N215

"SEVENTY-FIVE" LOW LUSTRE HOUSE PAINT

(FORMERLY "75" EXTERIOR EGGSHELL)

"Seventy-Five" Low Lustre house paint is highly pigmented, for exterior wood siding and wood shingles. May be used also over properly primed masonry and metal. Available in standard colors and three types of white: self-cleaning White; CC White for Controlled Chalking—trim work, etc.; and White Bases No. 1, 2, and 3 (for tinting only) for body or trim work.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. Sand under eaves and protected areas, **wash with detergent and thoroughly rinse.**

Priming — Prime new wood, new wood shingles, and prime or spot prime previous paint in poor condition with "75" House Paint Priming White. Prime new masonry with alkali-resistant "A-R" Primer. Prime bare metal with Flexico Metal Primer. Etch galvanized metal before priming. Tint primers toward topcoat color.

Tinting — Tint White Bases No. 1, 2, and 3 with Tone-All Universal Tinting Colors according to O'Brien Symphonic Color System formulas. Do not use alkali-sensitive colorants Orange, Medium Yellow, and Medium Green on masonry surfaces unless sealed with alkali-resistant primer.

Application — Stir well. Apply over a dry surface at temperature not less than 60° F. (Note: Apply only one coat—reduced with one pint of linseed oil per gallon—over previously painted wood shingles.) If required, thin sparingly with "75" Low Lustre Thinner, working limited areas to maintain a wet edge. Avoid brushing back into semi-dried film which creates lap marks. Allow 48 hours good drying weather between coats. — (PYOW)

CAUTION! COMBUSTIBLE! CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

"75" EGGSHELL GREEN BALSAM

Pigment	39.57%
18% Leaded Zinc Oxide	25.43%
Chromium Oxide	24.71%
Carbon Black	1.94%
Phthalocyanine Green	.45%
Silicates	47.47%
	100.00%
Vehicle	60.43%
Modified Soya Alkyd Resin	5.56%
Heat Processed Linseed Oil	29.35%
Aromatic Hydrocarbons	9.71%
Mineral Spirits & Driers	55.38%
	100.00%

SINCE O'BRIEN 1875

MADE BY THE O'BRIEN CORPORATION

SOUTH BEND IND • BALTIMORE MD • OKLAHOMA CITY OKLA • LOS ANGELES CAL • BRUNSWICK GA

49 TOC 001728

REGISTERED
REG'N. No. 7513B
DATE 5-13-68

O'BRIEN

"SEVENTY-FIVE"®
Gloss
HOUSE PAINT

PRIMING WHITE

ONE GALLON

49 TOC 001729

"SEVENTY-FIVE" LOW LUSTRE HOUSE PAINT

(FORMERLY "75" EXTERIOR EGGSHELL)

"Seventy-Five" Low Lustre house paint is highly pigmented, for exterior wood siding and wood shingles. May be used also over properly primed masonry and metal. Available in standard colors and three types of white: self-cleaning White; CC White for Controlled Chalking—trim work, etc.; and White Bases No. 1, 2, and 3 (for tinting only) for body or trim work.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. Sand under eaves and protected areas, **wash with detergent and thoroughly rinse.**

Priming — Prime new wood, new wood shingles, and prime or spot prime previous paint in poor condition with "75" House Paint Priming White. Prime new masonry with alkali-resistant "A-R" Primer. Prime bare metal with Flexico Metal Primer. Etch galvanized metal before priming. Tint primers toward topcoat color.

Tinting — Tint White Bases No. 1, 2, and 3 with Tone-All Universal Tinting Colors according to O'Brien Symphonic Color System formulas. Do not use alkali-sensitive colorants Orange, Medium Yellow, and Medium Green on masonry surfaces unless sealed with alkali-resistant primer.

Application — Stir well. Apply over a dry surface at temperature not less than 60° F. (Note: Apply only one coat—reduced with one pint of linseed oil per gallon—over previously painted wood shingles.) If required, thin sparingly with "75" Low Lustre Thinner, working limited areas to maintain a wet edge. Avoid brushing back into semi-dried film which creates lap marks. Allow 48 hours good drying weather between coats. — (PYOW)

CAUTION! COMBUSTIBLE! CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

"75" EGGSHELL GREEN BALSAM

Pigment	39.57%
18% Leaded Zinc Oxide	25.43%
Chromium Oxide	24.71%
Carbon Black	1.94%
Phtholocyanine Green	.45%
Silicates	47.47%
	100.00%
Vehicle	60.43%
Modified Soya Alkyd Resin	5.56%
Heat Processed Linseed Oil	29.35%
Aromatic Hydrocarbons	9.71%
Mineral Spirits & Driers	55.38%
	100.00%

SINCE O'BRIEN 1875

MADE BY THE O'BRIEN CORPORATION

SOUTH BEND IND • BALTIMORE MD • OKLAHOMA CITY OKLA • LOS ANGELES CAL • BRUNSWICK GA

49 TOC 001730

REGISTERED
REG'N. No. 5-13-68
DATE 7513/3

O'BRIEN

"SEVENTY-FIVE"®
Gloss
HOUSE PAINT

NILE GREEN

ONE GALLON

49 TOC 001731

"SEVENTY-FIVE" LOW LUSTRE HOUSE PAINT

(FORMERLY "75" EXTERIOR EGGSHELL)

"Seventy-Five" Low Lustre house paint is highly pigmented, for exterior wood siding and wood shingles. May be used also over properly primed masonry and metal. Available in standard colors and three types of white: self-cleaning White; CC White for Controlled Chalking—trim work, etc.; and White Bases No. 1, 2, and 3 (for tinting only) for body or trim work.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. Sand under eaves and protected areas, **wash with detergent and thoroughly rinse.**

Priming — Prime new wood, new wood shingles, and prime or spot prime previous paint in poor condition with "75" House Paint Priming White. Prime new masonry with alkali-resistant "A-R" Primer. Prime bare metal with Flexico Metal Primer. Etch galvanized metal before priming. Tint primers toward topcoat color.

Tinting — Tint White Bases No. 1, 2, and 3 with Tone-All Universal Tinting Colors according to O'Brien Symphonic Color System formulas. Do not use alkali-sensitive colorants Orange, Medium Yellow, and Medium Green on masonry surfaces unless sealed with alkali-resistant primer.

Application — Stir well. Apply over a dry surface at temperature not less than 60° F. (Note: Apply only one coat—reduced with one pint of linseed oil per gallon—over previously painted wood shingles.) If required, thin sparingly with "75" Low Lustre Thinner, working limited areas to maintain a wet edge. Avoid brushing back into semi-dried film which creates lap marks. Allow 48 hours good drying weather between coats. — (PYOW)

CAUTION! COMBUSTIBLE! CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

"75" EGGSHELL GREEN BALSAM

Pigment	39.57%
18% Leaded Zinc Oxide	25.43%
Chromium Oxide	24.71%
Carbon Black	1.94%
Phthalocyanine Green	.45%
Silicates	47.47%
	100.00%
Vehicle	60.43%
Modified Soya Alkyd Resin	5.56%
Heat Processed Linseed Oil	29.35%
Aromatic Hydrocarbons	9.71%
Mineral Spirits & Driers	55.38%
	100.00%

SINCE O'BRIEN 1875

MADE BY THE O'BRIEN CORPORATION

SOUTH BEND IND • BALTIMORE MD • OKLAHOMA CITY OKLA • LOS ANGELES CAL • BRUNSWICK GA

49 TOC 001732

O'BRIEN

"SEVENTY-FIVE"®

Gloss HOUSE PAINT

MEADOW GREEN

ONE GALLON

49 TOC 001733

"SEVENTY-FIVE" LOW LUSTRE HOUSE PAINT

(FORMERLY "75" EXTERIOR EGGSHELL)

"Seventy-Five" Low Lustre house paint is highly pigmented, for exterior wood siding and wood shingles. May be used also over properly primed masonry and metal. Available in standard colors and three types of white: self-cleaning White; CC White for Controlled Chalking—trim work, etc.; and White Bases No. 1, 2, and 3 (for tinting only) for body or trim work.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. Sand under eaves and protected areas, **wash with detergent and thoroughly rinse.**

Priming — Prime new wood, new wood shingles, and prime or spot prime previous paint in poor condition with "75" House Paint Priming White. Prime new masonry with alkali-resistant "A-R" Primer. Prime bare metal with Flexico Metal Primer. Etch galvanized metal before priming. Tint primers toward topcoat color.

Tinting — Tint White Bases No. 1, 2, and 3 with Tone-All Universal Tinting Colors according to O'Brien Symphonic Color System formulas. Do not use alkali-sensitive colorants Orange, Medium Yellow, and Medium Green on masonry surfaces unless sealed with alkali-resistant primer.

Application — Stir well. Apply over a dry surface at temperature not less than 60° F. (Note: Apply only one coat—reduced with one pint of linseed oil per gallon—over previously painted wood shingles.) If required, thin sparingly with "75" Low Lustre Thinner, working limited areas to maintain a wet edge. Avoid brushing back into semi-dried film which creates lap marks. Allow 48 hours good drying weather between coats. — (PYOW)

CAUTION! COMBUSTIBLE! CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

"75" EGGSHELL GREEN BALSAM

Pigment	39.57%
18% Leaded Zinc Oxide	25.43%
Chromium Oxide	24.71%
Carbon Black	1.94%
Phthalocyanine Green	.45%
Silicates	47.47%
	100.00%
Vehicle	60.43%
Modified Soya Alkyd Resin	5.56%
Heat Processed Linseed Oil	29.33%
Aromatic Hydrocarbons	9.71%
Mineral Spirits & Driers	55.38%
	100.00%

SINCE O'BRIEN 1875

MADE BY THE O'BRIEN CORPORATION

SOUTH BEND IND • BALTIMORE MD • OKLAHOMA CITY OKLA • LOS ANGELES CAL • BRUNSWICK GA

49 TOC 001734

O'BRIEN

REGISTERED
REG'N. No. 75313
DATE 5-13-68

"SEVENTY-FIVE"®
Gloss
HOUSE PAINT

RIPPLE GREEN

ENAMELIZED TRIM COLOR ONE GALLON

49 TOC 001735

"SEVENTY-FIVE" LOW LUSTRE HOUSE PAINT

(FORMERLY "75" EXTERIOR EGGSHELL)

"Seventy-Five" Low Lustre house paint is highly pigmented, for exterior wood siding and wood shingles. May be used also over properly primed masonry and metal. Available in standard colors and three types of white: self-cleaning White; CC White for Controlled Chalking—trim work, etc.; and White Bases No. 1, 2, and 3 (for tinting only) for body or trim work.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. Sand under eaves and protected areas, **wash with detergent and thoroughly rinse.**

Priming — Prime new wood, new wood shingles, and prime or spot prime previous paint in poor condition with "75" House Paint Priming White. Prime new masonry with alkali-resistant "A-R" Primer. Prime bare metal with Flexico Metal Primer. Etch galvanized metal before priming. Tint primers toward topcoat color.

Tinting — Tint White Bases No. 1, 2, and 3 with Tone-All Universal Tinting Colors according to O'Brien Symphonic Color System formulas. Do not use alkali-sensitive colorants Orange, Medium Yellow, and Medium Green on masonry surfaces unless sealed with alkali-resistant primer.

Application — Stir well. Apply over a dry surface at temperature not less than 60° F. (Note: Apply only one coat—reduced with one pint of linseed oil per gallon—over previously painted wood shingles.) If required, thin sparingly with "75" Low Lustre Thinner, working limited areas to maintain a wet edge. Avoid brushing back into semi-dried film which creates lap marks. Allow 48 hours good drying weather between coats. — (PYOW)

CAUTION! COMBUSTIBLE! CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

"75" EGGSHELL GREEN BALSAM

Pigment	39.57%
18% Leaded Zinc Oxide	25.43%
Chromium Oxide	24.71%
Carbon Black	1.94%
Phthalocyanine Green	.45%
Silicates	47.47%
	100.00%
Vehicle	60.43%
Modified Soya Alkyd Resin	5.56%
Heat Processed Linseed Oil	29.35%
Aromatic Hydrocarbons	9.71%
Mineral Spirits & Driers	55.38%
	100.00%

SINCE O'BRIEN 1875

MADE BY THE O'BRIEN CORPORATION

SOUTH BEND IND • BALTIMORE MD • OKLAHOMA CITY OKLA • LOS ANGELES CAL • BRUNSWICK GA

49 TOC 001736

REGISTERED
REG'N. No. 57313
DATE 5-13-68

O'BRIEN

"SEVENTY-FIVE"®
Gloss
HOUSE PAINT

HOLLAND BLUE

ENAMELIZED TRIM COLOR ONE GALLON

49 TOC 001737

"SEVENTY-FIVE" LOW LUSTRE HOUSE PAINT

(FORMERLY "75" EXTERIOR EGGSHELL)

"Seventy-Five" Low Lustre house paint is highly pigmented, for exterior wood siding and wood shingles. May be used also over properly primed masonry and metal. Available in standard colors and three types of white: self-cleaning White; CC White for Controlled Chalking—trim work, etc.; and White Bases No. 1, 2, and 3 (for tinting only) for body or trim work.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. Sand under eaves and protected areas, **wash with detergent and thoroughly rinse.**

Priming — Prime new wood, new wood shingles, and prime or spot prime previous paint in poor condition with "75" House Paint Priming White. Prime new masonry with alkali-resistant "A-R" Primer. Prime bare metal with Flexico Metal Primer. Etch galvanized metal before priming. Tint primers toward topcoat color.

Tinting — Tint White Bases No. 1, 2, and 3 with Tone-All Universal Tinting Colors according to O'Brien Symphonic Color System formulas. Do not use alkali-sensitive colorants Orange, Medium Yellow, and Medium Green on masonry surfaces unless sealed with alkali-resistant primer.

Application — Stir well. Apply over a dry surface at temperature not less than 60° F. (Note: Apply only one coat—reduced with one pint of linseed oil per gallon—over previously painted wood shingles.) If required, thin sparingly with "75" Low Lustre Thinner, working limited areas to maintain a wet edge. Avoid brushing back into semi-dried film which creates lap marks. Allow 48 hours good drying weather between coats. — (PYOW)

CAUTION! COMBUSTIBLE! CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

"75" EGGSHELL GREEN BALSAM

Pigment	39.57%
18% Leaded Zinc Oxide	25.43%
Chromium Oxide	24.71%
Carbon Black	1.94%
Phthalocyanine Green	.45%
Silicates	47.47%
	100.00%
Vehicle	60.43%
Modified Soya Alkyd Resin	5.56%
Heat Processed Linseed Oil	29.35%
Aromatic Hydrocarbons	9.71%
Mineral Spirits & Driers	55.38%
	100.00%

SINCE O'BRIEN 1875

MADE BY THE O'BRIEN CORPORATION

SOUTH BEND IND • BALTIMORE MD • OKLAHOMA CITY OKLA • LOS ANGELES CAL • BRUNSWICK GA

49 TOC 001738

REGISTERED
REG'N. No. 5-13-68
DATE 15/3/13

O'BRIEN

"SEVENTY-FIVE"®
Gloss
HOUSE PAINT

GOLDENROD

ENAMELIZED TRIM COLOR ONE GALLON

49 TOC 001739

"SEVENTY-FIVE" LOW LUSTRE HOUSE PAINT

(FORMERLY "75" EXTERIOR EGGSHELL)

"Seventy-Five" Low Lustre house paint is highly pigmented, for exterior wood siding and wood shingles. May be used also over properly primed masonry and metal. Available in standard colors and three types of white: self-cleaning White; CC White for Controlled Chalking—trim work, etc.; and White Bases No. 1, 2, and 3 (for tinting only) for body or trim work.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. Sand under eaves and protected areas, **wash with detergent and thoroughly rinse.**

Priming — Prime new wood, new wood shingles, and prime or spot prime previous paint in poor condition with "75" House Paint Priming White. Prime new masonry with alkali-resistant "A-R" Primer. Prime bare metal with Flexico Metal Primer. Etch galvanized metal before priming. Tint primers toward topcoat color.

Tinting — Tint White Bases No. 1, 2, and 3 with Tone-All Universal Tinting Colors according to O'Brien Symphonic Color System formulas. Do not use alkali-sensitive colorants Orange, Medium Yellow, and Medium Green on masonry surfaces unless sealed with alkali-resistant primer.

Application — Stir well. Apply over a dry surface at temperature not less than 60° F. (Note: Apply only one coat—reduced with one pint of linseed oil per gallon—over previously painted wood shingles.) If required, thin sparingly with "75" Low Lustre Thinner, working limited areas to maintain a wet edge. Avoid brushing back into semi-dried film which creates lap marks. Allow 48 hours good drying weather between coats. — (PYOW)

CAUTION! COMBUSTIBLE! CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

"75" EGGSHELL GREEN BALSAM

Pigment	39.57%
18% Leaded Zinc Oxide	25.43%
Chromium Oxide	24.71%
Carbon Black	1.94%
Phthalocyanine Green	.45%
Silicates	47.47%
	100.00%
Vehicle	60.43%
Modified Soya Alkyd Resin	5.56%
Heat Processed Linseed Oil	29.35%
Aromatic Hydrocarbons	9.71%
Mineral Spirits & Driers	55.38%
	100.00%

SINCE O'BRIEN 1875

MADE BY THE O'BRIEN CORPORATION

SOUTH BEND IND • BALTIMORE MD • OKLAHOMA CITY OKLA • LOS ANGELES CAL • BRUNSWICK GA

49 TOC 001740

REGISTERED
REGTN. No. 7513B
DATE 5-13-68

O'BRIEN

"SEVENTY-FIVE"®
Gloss
HOUSE PAINT

EVERGREEN

ENAMELIZED TRIM COLOR ONE GALLON

49 TOC 001741

"SEVENTY-FIVE" LOW LUSTRE HOUSE PAINT

(FORMERLY "75" EXTERIOR EGGSHELL)

"Seventy-Five" Low Lustre house paint is highly pigmented, for exterior wood siding and wood shingles. May be used also over properly primed masonry and metal. Available in standard colors and three types of white: self-cleaning White; CC White for Controlled Chalking—trim work, etc.; and White Bases No. 1, 2, and 3 (for tinting only) for body or trim work.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. Sand under eaves and protected areas, **wash with detergent and thoroughly rinse.**

Priming — Prime new wood, new wood shingles, and prime or spot prime previous paint in poor condition with "75" House Paint Priming White. Prime new masonry with alkali-resistant "A-R" Primer. Prime bare metal with Flexico Metal Primer. Etch galvanized metal before priming. Tint primers toward topcoat color.

Tinting — Tint White Bases No. 1, 2, and 3 with Tone-All Universal Tinting Colors according to O'Brien Symphonic Color System formulas. Do not use alkali-sensitive colorants Orange, Medium Yellow, and Medium Green on masonry surfaces unless sealed with alkali-resistant primer.

Application — Stir well. Apply over a dry surface at temperature not less than 60° F. (Note: Apply only one coat—reduced with one pint of linseed oil per gallon—over previously painted wood shingles.) If required, thin sparingly with "75" Low Lustre Thinner, working limited areas to maintain a wet edge. Avoid brushing back into semi-dried film which creates lap marks. Allow 48 hours good drying weather between coats. — (PYOW)

CAUTION! COMBUSTIBLE! CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

"75" EGGSHELL GREEN BALSAM

Pigment	39.57%
18% Leaded Zinc Oxide	25.43%
Chromium Oxide	24.71%
Carbon Black	1.94%
Phthalocyanine Green	.45%
Silicates	47.47%
	100.00%
Vehicle	60.43%
Modified Soya Alkyd Resin	5.56%
Heat Processed Linseed Oil	29.35%
Aromatic Hydrocarbons	9.71%
Mineral Spirits & Driers	55.38%
	100.00%

SINCE O'BRIEN 1875

MADE BY THE O'BRIEN CORPORATION

SOUTH BEND IND • BALTIMORE MD • OKLAHOMA CITY OKLA • LOS ANGELES CAL • BRUNSWICK GA

49 TOC 001742

REGISTERED
REG'N. No. 75131B
DATE 5-13-68

O'BRIEN

"SEVENTY-FIVE"
Gloss
HOUSE PAINT

DARK SLATE

ENAMELIZED TRIM COLOR

ONE GALLON

49 TOC 001743

"SEVENTY-FIVE" LOW LUSTRE HOUSE PAINT

(FORMERLY "75" EXTERIOR EGGSHELL)

"Seventy-Five" Low Lustre house paint is highly pigmented, for exterior wood siding and wood shingles. May be used also over properly primed masonry and metal. Available in standard colors and three types of white: self-cleaning White; CC White for Controlled Chalking—trim work, etc.; and White Bases No. 1, 2, and 3 (for tinting only) for body or trim work.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. Sand under eaves and protected areas, **wash with detergent and thoroughly rinse.**

Priming — Prime new wood, new wood shingles, and prime or spot prime previous paint in poor condition with "75" House Paint Priming White. Prime new masonry with alkali-resistant "A-R" Primer. Prime bare metal with Flexico Metal Primer. Etch galvanized metal before priming. Tint primers toward topcoat color.

Tinting — Tint White Bases No. 1, 2, and 3 with Tone-All Universal Tinting Colors according to O'Brien Symphonic Color System formulas. Do not use alkali-sensitive colorants Orange, Medium Yellow, and Medium Green on masonry surfaces unless sealed with alkali-resistant primer.

Application — Stir well. Apply over a dry surface at temperature not less than 60° F. (Note: Apply only one coat—reduced with one pint of linseed oil per gallon—over previously painted wood shingles.) If required, thin sparingly with "75" Low Lustre Thinner, working limited areas to maintain a wet edge. Avoid brushing back into semi-dried film which creates lap marks. Allow 48 hours good drying weather between coats. — (PYOW)

CAUTION! COMBUSTIBLE! CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

"75" EGGSHELL GREEN BALSAM

Pigment	39.57%
18% Leaded Zinc Oxide	25.43%
Chromium Oxide	24.71%
Carbon Black	1.94%
Phthalocyanine Green	.45%
Silicates	47.47%
	100.00%
Vehicle	60.43%
Modified Soya Alkyd Resin	5.56%
Heat Processed Linseed Oil	29.35%
Aromatic Hydrocarbons	9.71%
Mineral Spirits & Driers	55.38%
	100.00%

SINCE O'BRIEN 1875

MADE BY THE O'BRIEN CORPORATION

SOUTH BEND IND • BALTIMORE MD • OKLAHOMA CITY OKLA • LOS ANGELES CAL • BRUNSWICK GA

49 TOC 001744

O'BRIEN

"SEVENTY-FIVE"®

Gloss

HOUSE PAINT

DARK GREEN

ENAMELIZED TRIM COLOR

ONE GALLON

49 TOC 001745

"SEVENTY-FIVE" LOW LUSTRE HOUSE PAINT

(FORMERLY "75" EXTERIOR EGGSHELL)

"Seventy-Five" Low Lustre house paint is highly pigmented, for exterior wood siding and wood shingles. May be used also over properly primed masonry and metal. Available in standard colors and three types of white: self-cleaning White; CC White for Controlled Chalking—trim work, etc.; and White Bases No. 1, 2, and 3 (for tinting only) for body or trim work.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. Sand under eaves and protected areas, **wash with detergent and thoroughly rinse.**

Priming — Prime new wood, new wood shingles, and prime or spot prime previous paint in poor condition with "75" House Paint Priming White. Prime new masonry with alkali-resistant "A-R" Primer. Prime bare metal with Flexico Metal Primer. Etch galvanized metal before priming. Tint primers toward topcoat color.

Tinting — Tint White Bases No. 1, 2, and 3 with Tone-All Universal Tinting Colors according to O'Brien Symphonic Color System formulas. Do not use alkali-sensitive colorants Orange, Medium Yellow, and Medium Green on masonry surfaces unless sealed with alkali-resistant primer.

Application — Stir well. Apply over a dry surface at temperature not less than 60° F. (Note: Apply only one coat—reduced with one pint of linseed oil per gallon—over previously painted wood shingles.) If required, thin sparingly with "75" Low Lustre Thinner, working limited areas to maintain a wet edge. Avoid brushing back into semi-dried film which creates lap marks. Allow 48 hours good drying weather between coats. — (PYOW)

CAUTION! COMBUSTIBLE! CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

"75" EGGSHELL GREEN BALSAM

Pigment	39.57%
18% Leaded Zinc Oxide	25.43%
Chromium Oxide	24.71%
Carbon Black	1.94%
Phthalocyanine Green	.45%
Silicates	47.47%
	100.00%
Vehicle	60.43%
Modified Soya Alkyd Resin	5.56%
Heat Processed Linseed Oil	29.35%
Aromatic Hydrocarbons	9.71%
Mineral Spirits & Driers	55.38%
	100.00%

SINCE O'BRIEN 1875

MADE BY THE O'BRIEN CORPORATION

SOUTH BEND IND • BALTIMORE MD • OKLAHOMA CITY OKLA • LOS ANGELES CAL • BRUNSWICK GA

49 TOC 001746

REGISTERED

REG'N. No. 7513B

DATE 5-13-68

O'BRIEN

"SEVENTY-FIVE"®

Gloss

HOUSE PAINT

DARK BROWN

ENAMELIZED TRIM COLOR

ONE GALLON

49 TOC 001747

"SEVENTY-FIVE" LOW LUSTRE HOUSE PAINT

(FORMERLY "75" EXTERIOR EGGSHELL)

"Seventy-Five" Low Lustre house paint is highly pigmented, for exterior wood siding and wood shingles. May be used also over properly primed masonry and metal. Available in standard colors and three types of white: self-cleaning White; CC White for Controlled Chalking—trim work, etc.; and White Bases No. 1, 2, and 3 (for tinting only) for body or trim work.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. Sand under eaves and protected areas, **wash with detergent and thoroughly rinse.**

Priming — Prime new wood, new wood shingles, and prime or spot prime previous paint in poor condition with "75" House Paint Priming White. Prime new masonry with alkali-resistant "A-R" Primer. Prime bare metal with Flexico Metal Primer. Etch galvanized metal before priming. Tint primers toward topcoat color.

Tinting — Tint White Bases No. 1, 2, and 3 with Tone-All Universal Tinting Colors according to O'Brien Symphonic Color System formulas. Do not use alkali-sensitive colorants Orange, Medium Yellow, and Medium Green on masonry surfaces unless sealed with alkali-resistant primer.

Application — Stir well. Apply over a dry surface at temperature not less than 60° F. (Note: Apply only one coat—reduced with one pint of linseed oil per gallon—over previously painted wood shingles.) If required, thin sparingly with "75" Low Lustre Thinner, working limited areas to maintain a wet edge. Avoid brushing back into semi-dried film which creates lap marks. Allow 48 hours good drying weather between coats. — (PYOW)

CAUTION! COMBUSTIBLE! CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

"75" EGGSHELL GREEN BALSAM

Pigment	39.57%
18% Leaded Zinc Oxide	25.43%
Chromium Oxide	24.71%
Carbon Black	1.94%
Phthalocyanine Green	.45%
Silicates	47.47%
	100.00%
Vehicle	60.43%
Modified Soya Alkyd Resin	5.56%
Heat Processed Linseed Oil	29.35%
Aromatic Hydrocarbons	9.71%
Mineral Spirits & Driers	55.38%
	100.00%

SINCE O'BRIEN 1875

MADE BY THE O'BRIEN CORPORATION

SOUTH BEND IND • BALTIMORE MD • OKLAHOMA CITY OKLA • LOS ANGELES CAL • BRUNSWICK GA

49 TOC 001748